OCPP 1.6 Subset Certificate



Certificate holder: MODERNTEC Co., Ltd

Certificate number: OCA.0016.0393.CS

Product type: Charging Station

Product designation: MC-MS240A-1A

OCPP Software version: 1.0.0

Hardware feature set as stated below

Certification date: June 30, 2023

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol covered by this certificate can be found in the abstract of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association, June 30, 2023	(KSGA)Moderntec_Test Report template_MC-MS240A-1A_230629

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON



Abstract of test report

Test Result Summary

Test laboratory:	Korea Smart Grid Association		
Location:	Seoul , Korea		
Test Report Reference:	KSGA-OCPP1.6TEST-098-2023		
Vendor name:	MODERNTEC Co., Ltd		
Device Under Test:	Charging Station		
Communication:	JSON		
OCPP Software version:	1.0.0		
Test Result Summary	for the ce	ertified functionalities	
Functionalities	OCPP 1.6 Certification Test Results	Description	
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.	
Optional features			
Firmware Management	N/A	Support for (remote) firmware update management and diagnostic log file download.	
Smart Charging	N/A	Support for Smart Charging (all profile types, including stacking), to control charging.	
Reservation	N/A	Support for reservation of a connector of a Charging Station.	
Local Authorization List Managemen	Pass	Features to manage a local list in the charging station containing authorization data for whitelisting users.	
Remote Trigger	N/A	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.	

Test Report OCPP 1.6 Certification

Page 1 from 4



Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	60s	0:00:028	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	10s	00:00:04	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	10s	00:00:00	The response time for the RemoteStartTransaction message.

Test Configuration

Vendor	MODERNTEC Co., Ltd
DUT / SUT	Charging Station
Communication	JSON
Туре	MC-MS240A-1A
OCPP Software version	1.0.0
OCTT version	OCTT 1.6 v1.4.3

Hardware feature set			
Feature Configuration			
Single			
<yes></yes>			
Ethernet			
Single			
	Configuration Single <yes> Ethernet</yes>		

	Non-OCPP Charge Point	Configuration
Configuration key		Value
<>		<>



Configuration key Value Allow OfflineTxForUnknownId TRUE AuthorizationCacheEnabled FALSE AuthorizeRemoteTxRequests TRUE BlinkRepeat 60 ClockAlignedDataInterval 15 ConnectionTimeOut 30 ConnectorPhaseRotation - ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 20 HeartbeatInterval 60 LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAmpledData - MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionOnlevSideDisconnect TRUE StopTransactionOnlevalidId FALSE
Allow OfflineTxForUnknownId TRUE AuthorizationCacheEnabled FALSE AuthorizeRemoteTxRequests TRUE BlinkRepeat 60 ClockAlignedDataInterval 15 ConnectionTimeOut 30 ConnectorPhaseRotation - ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 20 HeartbeatInterval 60 LightIntensity 60 LocalPathorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionOnEVSideDisconnect TRUE
AuthorizeRemoteTxRequests TRUE BlinkRepeat 60 ClockAlignedDataInterval 15 ConnectionTimeOut 30 ConnectorPhaseRotation - ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 20 HeartbeatInterval 60 LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedData - MeterValuesSampledData - MeterValueSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
AuthorizeRemoteTxRequests TRUE BlinkRepeat 60 ClockAlignedDataInterval 15 ConnectionTimeOut 30 ConnectorPhaseRotation - ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 20 HeartbeatInterval 60 LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedData - MeterValuesSampledData - MeterValueSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
BlinkRepeat 60 ClockAlignedDataInterval 15 ConnectionTimeOut 30 ConnectorPhaseRotation - ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 20 HeartbeatInterval 60 LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedData - MeterValuesSampledData - MeterValueSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
ClockAlignedDataInterval 15 ConnectionTimeOut 30 ConnectorPhaseRotation - ConnectorPhaseRotationMaxLength - ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 20 HeartbeatInterval 60 LightIntensity 60 LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedData - MeterValuesSampledData - MeterValueSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
ConnectionTimeOut 30 ConnectorPhaseRotation - ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 20 HeartbeatInterval 60 LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedData - MeterValuesSampledDataMaxLength 20 MeterValueSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
ConnectorPhaseRotation - ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 20 HeartbeatInterval 60 LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedData - MeterValuesSampledDataMaxLength 20 MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
GetConfigurationMaxKeys 20 HeartbeatInterval 60 LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedData 20 MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
GetConfigurationMaxKeys 20 HeartbeatInterval 60 LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedData 20 MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
HeartbeatInterval 60 LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 20 MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
LightIntensity 60 LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 20 MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
LocalAuthorizeOffline TRUE LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 20 MeterValuesSampledDataMaxLength 20 MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
LocalPreAuthorize FALSE MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 20 MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
MaxEnergyOnInvalidId 60 MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 20 MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 20 MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 20 MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
MeterValuesAlignedDataMaxLength 20 MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
MeterValuesSampledData - MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
MeterValuesSampledDataMaxLength 20 MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
MeterValueSampleInterval 150 MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
MinimumStatusDuration 0 NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
NumberOfConnectors 1 ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
ResetRetries 0 StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
StopTransactionMaxMeterValues 150 StopTransactionOnEVSideDisconnect TRUE
StopTransactionOnEVSideDisconnect TRUE
StopTxnAlignedData -
StopTxnAlignedDataMaxLength 20
StopTxnSampledData -
StopTxnSampledDataMaxLength 20
SupportedFeatureProfiles Core,LocalAuthListManagement
SupportedFeatureProfilesMaxLength -
TransactionMessageAttempts 0
TransactionMessageRetryInterval 60
UnlockConnectorOnEVSideDisconnect FALSE
WebSocketPingInterval 60
LocalAuthListEnabled TRUE
LocalAuthListMaxLength 60
SendLocalListMaxLength 60
ReserveConnectorZeroSupported -
ChargeProfileMaxStackLevel -
ChargingScheduleAllowedChargingRateUnit -
ChargingScheduleMaxPeriods -
ConnectorSwitch3to1PhaseSupported -
MaxChargingProfilesInstalled -
· · · · · · · · · · · · · · · · · · ·

Page 3 from 4



Statement of Approval

Vendor		Date: 2023.06.30
Name	Seongdoo Kim	Signature
Company	MODERNTEC Co., Ltd	
Department	Representative Director	Samuel Vin
Position	Chief Executive Officer	Seongdoo Kim
Location	Seoul, Korea	

Test laboratory			Date: 2023.06.30
Name	Philip YANG		Signature
Company	Korea Smart Grid Association		la
Department	Quality Certification Center		
Position	Chief Researcher	Γ	
Location	Seoul, Korea		/