OCPP 1.6 Full Certificate



Certificate holder: EVSIS Co., Ltd

Certificate number: OCA.0016.0444.CS

Product type: Charging Station

Product designation: JC-9931-100-C4

OCPP Software version: 0.0.1

Hardware feature set as stated below

Certification date: July 21, 2023

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol are also covered by this certification.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association, July 21, 2023	(KSGA)EVSIS_Test Report template_JC-9931-100-C4_230721

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON Chairman



Abstract of test report

Test Result Summary

Test Report OCPP 1.6 Certification			
Test laboratory:	Korea Smart Grid Association		
Location:	Seoul , Korea		
Test Report Reference: KSGA-OCPP1.6TEST-135-2023			
Vendor name:	EVSIS Co., Ltd.		
Device Under Test: Charging Station			
Communication:	JSON		
OCPP Software version:	0.0.1		
Test Result Summary for the certified functionalities			

OCFF SOftware version.	0.0.1	
Test Result Summary	for the ce	ertified functionalities
Functionalities	OCPP 1.6 Certification Test Results	Description
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.
Optional features		
Firmware Management	Pass	Support for (remote) firmware update management and diagnostic log file download.
Smart Charging	Pass	Support for Smart Charging (all profile types, including stacking), to control charging.
Reservation	Pass	Support for reservation of a connector of a Charging Station.
Local Authorization List Managemen	Pass	Features to manage a local list in the charging station containing authorization data for whitelisting users.
Remote Trigger	Pass	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.

Page 1 from 4



Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	120s	0:01:43	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	10s	00:00:01	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	10s	00:00:00	The response time for the RemoteStartTransaction message.

Test Configuration

Vendor	EVSIS Co., Ltd.
DUT / SUT	Charging Station
Communication	JSON
Туре	JC-9931-100-C4
OCPP Software version	0.0.1
OCTT version	OCTT 1.6 v1.4.3

Hardware feature set			
Feature Configuration			
Socket(s) / connector(s)	Single		
Fixed cable	<yes></yes>		
Communication technology	Ethernet		
RFID readers	Single		

Non-OCPP Charge Point Configuration			
Configuration key	Value		
<>	<>		

timestamps.



OCPP Charging Station	Configuration		
Configuration key	Value		
AllowOfflineTxForUnknownId	TRUE		
AuthorizationCacheEnabled	FALSE		
AuthorizeRemoteTxRequests	TRUE		
BlinkRepeat	0		
ClockAlignedDataInterval	0		
ConnectionTimeOut	30		
ConnectorPhaseRotation	RST		
ConnectorPhaseRotationMaxLength	-		
GetConfigurationMaxKeys	3		
HeartbeatInterval	20		
LightIntensity	20		
LocalAuthorizeOffline	TOUE		
LocalAuthorize LocalPreAuthorize	TRUE		
	TRUE		
MaxEnergyOnInvalidId	-		
MessageTimeout	-		
MeterValuesAlignedData	Energy.Active.Import.Register		
MeterValuesAlignedDataMaxLength	8		
	CurrentImport, CurrentOffered,		
MeterValuesSampledData	Energy.Active.Import.Register,		
Meter values pampied pata	Power.Active.Import, Power.Offered		
	SoC, Voltage		
MeterValuesSampledDataMaxLength	8		
MeterValueSampleInterval	15		
MinimumStatusBuration			
NumberOfConnectors	1		
ResetRetries	3		
StopTransactionMaxMeterValues	<u> </u>		
StopTransactionOnEVSideDisconnect	TRUE		
StopTransactionOnInvalidId			
Stop transaction on invalidid	TRUE		
	CurrentImport, CurrentOffered,		
	Energy.Active.Import.Register,		
StopTxnAlignedData	Energy.Active.Import.Interval,		
	Power.Active.Import, Power.Offered		
	SoC, Voltage		
StopTxnAlignedDataMaxLength	8		
	CurrentImport, CurrentOffered,		
Contract of Deco	Energy.Active.Import.Register,		
StopTxnSampledData	Power.Active.Import, Power.Offered		
	SoC, Voltage		
StopTxnSampledDataMaxLength	8		
	Core, Firmware Management, Local Au		
SupportedFeatureProfiles	hListManagement, Reservation, Smart		
Supported eather follies			
SupportedFeatureProfilesMaxLength	harging,RemoteTrigger		
- · · ·	6		
TransactionMessageAttempts	2		
TransactionMessageRetryInterval	30		
UnlockConnectorOnEVSideDisconnect	FALSE		
WebSocketPingInterval	0		
WebSocketPingInterval			
-	-		
LocalAuthListEnabled	FALSE		
LocalAuthListEnabled LocalAuthListMaxLength	FALSE 100000		
LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength	FALSE 100000 100		
LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength	FALSE 100000		
LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported	FALSE 100000 100		
LocalAuthListEnabled LocalAuthListMaxLength BesdLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel	FALSE 100000 100 FALSE		
WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods	FALSE 100000 100 FALSE 5		
LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods	FALSE 100000 100 FALSE 5 Ampère & Watt		
LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods ConnectorSwitch3to1PhaseSupported	FALSE 100000 100 FALSE 5 Ampère & Watt 24		
LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods	FALSE 100000 100 FALSE 5 Ampère & Watt		

Page 3 from 4



Statement of Approval

Vendor			Date: 2023.07.21
Name	Su-jin Kim		Signature
Company	EVSIS Co.,Ltd.		
Department	Software convergence team		L/
Position	Researcher		
Location	Goyang, Korea		ę.

Test laboratory			Date: 2023.07.21
Name	Philip YANG		Signature
Company	Korea Smart Grid Association		La
Department	ment Quality Certification Center		
Position	ion Chief Researcher		
Location	Seoul, Korea		