OCPP 1.6 Full Certificate



Certificate holder: EVSIS Co., Ltd

Certificate number: OCA.0016.0446.CS

Product type: Charging Station

Product designation: JC-92B1-7-01B

OCPP Software version: 0.0.1

Hardware feature set as stated below

Certification date: July 21, 2023

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol are also covered by this certification.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association, July 21, 2023	(KSGA)EVSIS_Test Report template_JC-92B1-7-01B_230721

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON Chairman



Abstract of test report

Test Result Summary

Test Report OCPP 1.6 Certification				
Test laboratory: Korea Smart Grid Association				
Location: Seoul , Korea				
Test Report Reference: KSGA-OCPP1.6TEST-134-2023				
Vendor name:	EVSIS Co., Ltd.			
Device Under Test:	Charging Station			
Communication: JSON				
OCPP Software version:	0.0.1			
Test Result Summary for the certified functionalities				

Test Result Summary	for the ce	ertified functionalities
Functionalities	OCPP 1.6 Certification Test Results	Description
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.
Optional features		
Firmware Management	Pass	Support for (remote) firmware update management and diagnostic log file download.
Smart Charging	Pass	Support for Smart Charging (all profile types, including stacking), to control charging.
Reservation	Pass	Support for reservation of a connector of a Charging Station.
Local Authorization List Managemen	Pass	Features to manage a local list in the charging station containing authorization data for whitelisting users.
Remote Trigger	Pass	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.

Page 1 from 4



Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	120s	0:01:04	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	10s	00:00:01	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	10s	00:00:01	The response time for the RemoteStartTransaction message.

Test Configuration

Vendor	EVSIS Co., Ltd.
DUT / SUT	Charging Station
Communication	JSON
Туре	JC-92B1-7-01B
OCPP Software version	0.0.1
OCTT version	OCTT 1.6 v1.4.3

Hardware feature set				
Feature Configuration				
Socket(s) / connector(s)	Single			
Fixed cable	<yes></yes>			
Communication technology	Ethernet			
RFID readers	Single			

Non-OCPP Charge Point Configuration		
Configuration key		Value
<>		<>

All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:			
Limit / setting Value			
Device supports sending milliseconds in timestamps. Yes			



	Configuration
Configuration key	Value
AllowOfflineTxForUnknownId	FALSE
AuthorizationCacheEnabled	FALSE
	FALSE
AuthorizeRemoteTxRequests	FALSE
BlinkRepeat	•
Clock Aligned DataInterval	0
ConnectionTimeOut	60
ConnectorPhaseRotation	RST
ConnectorPhaseRotationMaxLength	10
GetConfigurationMaxKeys	11
HeartbeatInterval	20
	20
LightIntensity	
LocalAuthorizeOffline	TRUE
LocalPreAuthorize	TRUE
MaxEnergyOnInvalidId	-
MessageTimeout	-
	Current.Import, Current.Offered,
	Energy.Active.Import.Register,
Material shape Alienad Date	
MeterValuesAlignedData	Energy.Active.Import.Interval,
	Power.Active.Import,
	Power.Offered, SoC, Voltage
MeterValuesAlignedDataMaxLength	8
	Current.Offered, Voltage,
	Energy.Active.Import.Register,
MeterValuesSampledData	
·	Power.Offered,Current.Import,Po
	er.Active.Import
MeterValuesSampledDataMaxLength	8
MeterValueSampleInterval	300
MinimumStatusDuration	_
NumberOfConnectors	1
ResetRetries	1
StopTransactionMaxMeterValues	-
StopTransactionOnEVSideDisconnect	TRUE
StopTransactionOnInvalidId	TRUE
	Current.Import, Current.Offered,
	· ·
	Energy.Active.Import.Register,
StopTxnAlignedData	Energy.Active.Import.Interval,
	Power.Active.Import,
	Power.Offered, SoC, Voltage
StopTxnAlignedDataMaxLength	8
, ,	Current.Import, Current.Offered,
StopTxnSampledData	Energy.Active.Import.Register,
	Power.Active.Import,
	Power.Offered, Voltage
StopTxnSampledDataMaxLength	8
	Core,FirmwareManagement,Loc
SupportedFeatureProfiles	AuthListManagement,Reservatio
	,SmartCharging,RemoteTrigger
Ourse and difference Depth 1997	6
SupportedFeatureProfilesMaxLength	
TransactionMessageAttempts	3
TransactionMessageAttempts	3
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect	3 30 TRUE
TransactionMessageAttempts TransactionMessageRetryInterval	3 30
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect	3 30 TRUE
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect	3 30 TRUE
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled	3 30 TRUE 300 FALSE
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength	3 30 TRUE 300 FALSE 100000
TransactionMessageAttempts TransactionMessagePetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength	3 30 TRUE 300 FALSE 100000
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength	3 30 TRUE 300 FALSE 100000
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported	3 30 TRUE 300 FALSE 100000 100 FALSE
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel	3 30 TRUE 300 FALSE 100000 100 FALSE
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit	3 30 TRUE 300 FALSE 100000 100 FALSE 5 Ampère & Watt
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel	3 30 TRUE 300 FALSE 100000 100 FALSE
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit	3 30 TRUE 300 FALSE 100000 100 FALSE 5 Ampère & Watt
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods	3 30 TRUE 300 FALSE 100000 100 FALSE 5 Ampère & Watt

Page 3 from 4



Statement of Approval

Vendor			Date: 2023.07.21
Name	Su-jin Kim		Signature
Company	ompany EVSIS Co.,Ltd.		
Department Software convergence team			56
Position Researcher			
Location	Goyang, Korea		ę.,

Test laboratory			Date: 2023.07.21
Name Philip YANG Signature		Signature	
Company	Company Korea Smart Grid Association		14
Department Quality Certification Center			
Position Chief Researcher			
Location	Seoul, Korea		