OCPP 1.6 Subset Certificate



Certificate holder: HiEV Charger

Certificate number: OCA.0016.0544.CS

Product type: Charging Station

Product designation: EVW007SK-SS

OCPP Software version: 1.01

Hardware feature set as stated below

Certification date: October 10, 2023

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 - Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol covered by this certificate can be found in the abstract of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association, October 10, 2023	(KSGA)HiEV Charger_Test Report template_EVW007SK-SS_231010

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON Chairman



Abstract of test report

Test Result Summary

Test Report OCPP 1.6 Certification					
Test laboratory:	Korea Smart Grid Association				
Location:	Seoul, Korea				
Test execution location:	HiEV Charger (Pyeongtaek, Korea)				
Test Report Reference:	KSGA-OCPP1.6TEST-173-2023				
Vendor name:	HiEV Charger				
Device Under Test:	Charging Station				
Communication:	JSON				
OCPP Software version:	1,01				
Product designation:	EVW007SK-SS				

Test Result Summary for the certified functionalities				
Functionalities	OCPP 1.6 Certification Test Results			
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.		
Optional features				
Firmware Management	N/A	Support for (remote) firmware update management and diagnostic log file download.		
Smart Charging	N/A	Support for Smart Charging (all profile types, including stacking), to control charging.		
Reservation	N/A	Support for reservation of a connector of a Charging Station.		
Local Authorization List Manageme	N/A	Features to manage a local list in the charging station containing authorization data for whitelisting users.		
Remote Trigger	N/A	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.		

Page 1 from 4



Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	60s	00:00:11	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are
OCPP response timeout:	60s	00:00:01	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	60s	00:00:00	The response time for the RemoteStartTransaction message.

Test Configuration

Vendor	HiEV Charger
DUT / SUT	Charging Station
Communication	JSON
Туре	EVW007SK-SS
OCPP Software version	1,01
OCTT version	OCTT 1.6 v1.4.3

Hardware feature set			
Feature	Configuration		
Socket(s) / connector(s)	Single		
Fixed cable	<yes></yes>		
Communication technology	Ethernet		
RFID readers	Single		

Non-OCPP Charge Point Configuration			
Configuration key		Value	
<>		<>	

All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:			
Limit / setting Value			
Device supports sending milliseconds in timestamps.	Yes		



OCPP Charging Station Configuration			
Configuration key	Value		
AllowOfflineTxForUnknownId	FALSE		
AuthorizationCacheEnabled	-		
AuthorizeRemoteTxRequests	TRUE		
BlinkRepeat	-		
ClockAlignedDataInterval	0		
ConnectionTimeOut	60		
ConnectorPhaseRotation	NotApplicable		
ConnectorPhaseRotationMaxLength	-		
GetConfigurationMaxKeys	21		
Heartbeatinterval	20		
LightIntensity	-		
LocalAuthorizeOffline	TRUE		
LocalPreAuthorize	FALSE		
MaxEnergyOnInvalidId	-		
MessageTimeout	_		
Meter Values Aligned Data	Current.Import, Current.Offered, Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperature, Voltage		
MeterValuesAlignedDataMaxLength			
Meter Values Sampled Data	Current.Import, Current.Offered, Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperature, Voltage		
MeterValuesSampledDataMaxLength			
Meter ValueSampleInterval	20		
MinimumStatusDuration	-		
NumberOfConnectors	1		
ResetRetries	1		
	·		
StopTransactionMaxMeterValues	- TOUE		
StopTransactionOnEVSideDisconnect StopTransactionOnInvalidId	TRUE TRUE		
StopTxnAlignedData	Current.Import, Current.Offered, Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperature, Voltage		
StopTxnAlignedDataMaxLength	voltage		
StopTxnSampledData	Current.Import, Current.Offered, Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperature, Voltage		
StopTxnSampledDataMaxLength	-		
SupportedFeatureProfiles	Core		
SupportedFeatureProfilesMaxLength	-		
TransactionMessageAttempts	3		
TransactionMessageRetryInterval	30		
UnlockConnectorOnEVSideDisconnect	FALSE		
WebSocketPingInterval	-		
LocalAuthListEnabled	-		
LocalAuthListMaxLength	-		
SendLocalListMaxLength	-		
ReserveConnectorZeroSupported	-		
ChargeProfileMaxStackLevel	-		
ChargingScheduleAllowedChargingRateUnit	-		
ChargingScheduleMaxPeriods	-		
ConnectorSwitch3to1PhaseSupported	-		
MaxChargingProfilesInstalled	-		
SupportedFileTransferProtocols	-		

Page 3 from 4



Statement of Approval

Vendor		П	Date: 2023.10.10	
Name	Dong Ju Kang			Signature
Company	HiEV Charger		T	
Department	-			THE
Position	CEO			事表加
Location	Pyeongtaek, Korea			

Test laboratory		Date : 2023.10.10
Name Philip YANG		Signature
Company Korea Smart Grid Association		4
Department	Quality Certification Center	
Position	Chief Researcher	
Location	Seoul, Korea	,