# OCPP 1.6 Subset Certificate



Certificate holder: HiEV Charger

Certificate number: OCA.0016.0545.CS

Product type: Charging Station

Product designation: EVW007SK-ST

OCPP Software version: 1.01

Hardware feature set as stated below

Certification date: October 10, 2023

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 - Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol covered by this certificate can be found in the abstract of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association, October 10, 2023	(KSGA)HiEV Charger_Test Report template_EVW007SK-ST_231010

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON Chairman



# **Abstract of test report**

Test Result Summary

Test R	eport OCPP 1.6 Certification		
Test R	eport der i 1:0 certification		
Test laboratory:	Korea Smart Grid Association		
Location:	Seoul, Korea		
Test execution location:	HiEV Charger (Pyeongtaek, Korea)		
Test Report Reference:	KSGA-OCPP1.6TEST-179-2023		
Vendor name:	HiEV Charger		
Device Under Test:	Charging Station		
Communication:	JSON		
OCPP Software version:	1,01		
Product designation:	EVW007SK-ST		
Test Result Summary for the certified functionalities			
Functionalities	OCPP 1.6 Description		
	Certification		

Test Result Summary	for the ce	rtified functionalities
Functionalities	OCPP 1.6 Certification Test Results	
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.
Optional features		
Firmware Management	N/A	Support for (remote) firmware update management and diagnostic log file download.
Smart Charging	N/A	Support for Smart Charging (all profile types, including stacking), to control charging.
Reservation	N/A	Support for reservation of a connector of a Charging Station.
Local Authorization List Managemen	N/A	Features to manage a local list in the charging station containing authorization data for whitelisting users.
Remote Trigger	N/A	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.

Page 1 from 4



#### Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	60s	00:00:11	The response time for when waiting for an OCPP function with its corresponding request message.  (Firmware update, Diagnostics and Reboot are
OCPP response timeout:	60s	00:00:01	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	60s	00:00:00	The response time for the RemoteStartTransaction message.

## Test Configuration

Vendor	HiEV Charger		
DUT / SUT	Charging Station		
Communication	JSON		
Туре	EVW007SK-ST		
OCPP Software version	1,01		
OCTT version	OCTT 1.6 v1.4.3		

Hardware feature set		
Feature	Configuration	
Socket(s) / connector(s)	Single	
Fixed cable	<yes></yes>	
Communication technology	Ethernet	
RFID readers	Single	

Non-OCPP Charge Point Configuration			
Configuration key		Value	
<>		<>	

All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:		
Limit / setting	Value	
Device supports sending milliseconds in timestamps.	Yes	



	Configuration
Configuration key	Value
AllowOfflineTxForUnknownId	FALSE
AuthorizationCacheEnabled	-
AuthorizeRemoteTxRequests	TRUE
BlinkRepeat	-
ClockAlignedDataInterval	0
ConnectionTimeOut	60
ConnectorPhaseRotation	NotApplicable
ConnectorPhaseRotationMaxLength	-
GetConfigurationMaxKeys	21
HeartbeatInterval	20
LightIntensity	-
LocalAuthorizeOffline	TRUE
LocalPreAuthorize	FALSE
MaxEnergyOnInvalidId	-
MessageTimeout	-
Meter Values Aligned Data	Current.Import, Current.Offered Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperatur Voltage
MeterValuesAlignedDataMaxLength	-
Meter Values Sampled Data	Current.Import, Current.Offered Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperatur Voltage
Meter Values Sampled Data Max Length	-
MeterValueSampleInterval	20
MinimumStatusDuration	-
NumberOfConnectors	1
ResetRetries	1
StopTransactionMaxMeterValues	-
StopTransactionOnEVSideDisconnect	TRUE
StopTransactionOnInvalidId	TRUE
StopTxnAlignedData	Current.Import, Current.Offered Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperatur Voltage
StopTxnAlignedDataMaxLength	-
	Current.Import, Current.Offered Energy.Active.Import.Register, Energy.Active.Import.Interval,
Stop Txn Sampled Data	Power.Offered, SoC, Temperatur Voltage
	Power.Offered, SoC, Temperatur
StopTxnSampledDataMaxLength	Power.Offered, SoC, Temperatur
Stop Txn Sampled Data Max Length Supported Feature Profiles	Power.Offered, SoC, Temperatur Voltage
Stop Txn Sampled Data Max Length Supported Feature Profiles Supported Feature Profiles Max Length	Power.Offered, SoC, Temperatur Voltage
Stop Txn Sampled Data Max Length Supported Feature Profiles Supported Feature Profiles Max Length Transaction Message Attempts	Power.Offered, SoC, Temperatur Voltage - Core
Stop Txn Sampled Data Max Length Supported Feature Profiles Supported Feature Profiles Max Length Transaction Message Attempts Transaction Message Retry Interval	Power.Offered, SoC, Temperatur Voltage - Core - 3
Stop Txn Sampled Data Max Length Supported Feature Profiles Supported Feature Profiles Max Length Transaction Message Attempts Transaction Message Retry Interval Unlock Connector On EV Side Disconnect	Power.Offered, SoC, Temperatur Voltage - Core - 3
StopTxnSampledDataMaxLength SupportedFeatureProfiles SupportedFeatureProfilesMaxLength TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval	Power.Offered, SoC, Temperatur Voltage  - Core - 3 30 FALSE
StopTxnSampledDataMaxLength SupportedFeatureProfiles SupportedFeatureProfilesMaxLength TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled	Power.Offered, SoC, Temperatur Voltage - Core - 3 30 FALSE -
StopTxnSampledDataMaxLength SupportedFeatureProfiles SupportedFeatureProfilesMaxLength TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength	Power.Offered, SoC, Temperatur Voltage  - Core - 3 30 FALSE
StopTxnSampledDataMaxLength SupportedFeatureProfiles SupportedFeatureProfilesMaxLength TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength	Power.Offered, SoC, Temperatur Voltage - Core - 3 30 FALSE -
StopTxnSampledDataMaxLength SupportedFeatureProfiles SupportedFeatureProfilesMaxLength TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported	Power.Offered, SoC, Temperatur Voltage - Core - 3 30 FALSE -
StopTxnSampledDataMaxLength SupportedFeatureProfiles SupportedFeatureProfilesMaxLength TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported	Power.Offered, SoC, Temperatur Voltage - Core - 3 30 FALSE -
StopTxnSampledData  StopTxnSampledDataMaxLength SupportedFeatureProfiles SupportedFeatureProfilesMaxLength TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit	Power.Offered, SoC, Temperatur Voltage - Core - 3 30 FALSE
StopTxnSampledDataMaxLength SupportedFeatureProfiles SupportedFeatureProfilesMaxLength TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel	Power.Offered, SoC, Temperatur Voltage  - Core - 3 30 FALSE
StopTxnSampledDataMaxLength SupportedFeatureProfiles SupportedFeatureProfilesMaxLength TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit	Power.Offered, SoC, Temperatur Voltage  - Core - 3 30 FALSE
StopTxnSampledDataMaxLength SupportedFeatureProfiles SupportedFeatureProfilesMaxLength TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods	Power.Offered, SoC, Temperatur Voltage  - Core - 3 30 FALSE

Page 3 from 4



## Statement of Approval

Vendor		Date: 2023.10.10
Name	Dong Ju Kang	Signature
Company	HiEV Charger	
Department	-	TEMENT
Position	CEO	事表加
Location	Pyeongtaek, Korea	

Test laboratory		<b>Date</b> : 2023.10.10
Name	Philip YANG	Signature
Company Korea Smart Grid Association		la.
Department	Quality Certification Center	
Position Chief Researcher		
Location	Seoul, Korea	, , , , , , , , , , , , , , , , , , ,