# OCPP 1.6 Subset Certificate



Certificate holder: Samsung EVC

Certificate number: OCA.0016.0129.CS

Product type: Charging Station

Product designation: SSEVC21S-CR7KW

OCPP Software version: 62.02.02

Hardware feature set as stated below

Certification date: May 2, 2022

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 - Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol covered by this certificate can be found in the abstract of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

| Applied tests   | Performed by / on                               | Document evidence                        |
|---|---|--|
| Conformance testing according to the test specification referenced by the test report | Korea Smart Grid<br>Association,<br>May 2, 2022 | KSGA_20220502_Test<br>Report_Samsung EVC |

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

Chairman Chairman



## **Abstract of test report**

#### Test Result Summary

| ult Summary                                  |   |  |  |
|--|---|--|--|
| Test Report                                  | OCPP 1.6                                  | Certification  |  |
| est laboratory: Korea Smart Grid Association |   |  |  |
| Location:                                    | Seoul , Korea                             |  |  |
| Test Report Reference:                       | KSGA-OCPP1.6TEST-063-2022                 |  |  |
| Vendor name:                                 | Samsung EVC                               |  |  |
| Device Under Test:                           | Charging Stati                            |  |  |
| Communication:                               | JSON                                      |  |  |
| OCPP Software version:                       | 62.02.02                                  |  |  |
| Test Result Summary                          | for the ce                                | rtified functionalities  |  |
| Functionalities                              | OCPP 1.6<br>Certification<br>Test Results | Description  |  |
| Core   | Pass                                      | Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.   |  |
| Optional features                            |   |  |  |
| Firmware Management                          | N/A                                       | Support for (remote) firmware update management and diagnostic log file download.  |  |
| Smart Charging                               | N/A                                       | Support for Smart Charging (all profile types, including stacking), to control charging.   |  |
| Reservation                                  | N/A                                       | Support for reservation of a connector of a Charging Station.  |  |
| Local Authorization List Manageme            | N/A                                       | Features to manage a local list in the charging station containing authorization data for whitelisting users.  |  |
| Remote Trigger                               | N/A                                       | Support for remotely triggering<br>messages that originate from a<br>Charging Station. This can be used for<br>resending messages or for getting the<br>latest information from the Charging |  |

Station.



#### Performance Measurement Results

| Performance Measurement Results       |            |                |   |
|---------------------------------------|------------|----------------|---|
| Name                                  | PICS value | Measured value | Description   |
| OCPP triggered function timeout:      | 2000s      | 00:00:17       | The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.) |
| OCPP response timeout:                | 2000s      | 00:00:01       | The response time for when waiting for an OCPP response message.  |
| Response time RemoteStartTransaction: | 500s       | 00:00:01       | The response time for the RemoteStartTransaction message.   |

#### **Test Configuration**

#### Test Configuration

| Vendor                | Samsung EVC      |  |  |
|-----------------------|------------------|--|--|
| DUT / SUT             | Charging Station |  |  |
| Communication         | JSON             |  |  |
| Туре                  | SSEVC21S-CR7KW   |  |  |
| OCPP Software version | 62.02.02         |  |  |
| OCTT version          | OCTT 1.6 v1.4.3  |  |  |

| Hardware feature set     |             |  |  |  |
|--------------------------|-------------|--|--|--|
| Feature Configuration    |             |  |  |  |
| Socket(s) / connector(s) | Single      |  |  |  |
| Fixed cable              | <yes></yes> |  |  |  |
| Communication technology | Wifi        |  |  |  |
| RFID readers             | Single      |  |  |  |

| Non-OCPP Charge Point Configuration |       |  |
|-------------------------------------|-------|--|
| Configuration key                   | Value |  |
| <>                                  | <>    |  |
|                                     |       |  |

| laboratory and for the correct functioning of the CSMS: |       |  |
|---|-------|--|
| Limit / setting   | Value |  |
| Device supports sending milliseconds in timestamps.     | Yes   |  |
| 11 3  | Yes   |  |



| Configuration key                            | Value |
|--|-------|
| Configuration key                            | value |
| AllowOfflineTxForUnknownId                   | -     |
| AuthorizationCacheEnabled                    | -     |
| AuthorizeRemoteTxRequests                    | FALSE |
| BlinkRepeat                                  | 1     |
| ClockAlignedDataInterval                     | 30    |
| ConnectionTimeOut                            | 180   |
| ConnectorPhaseRotation                       | 0     |
| ConnectorPhaseRotationMaxLength              | 128   |
| GetConfigurationMaxKeys                      | 21    |
| HeartbeatInterval                            | 180   |
| LightIntensity                               | 100   |
| LocalAuthorizeOffline                        | FALSE |
| LocalPreAuthorize                            | TRUE  |
| Max Energy On Invalid Id                     | 0     |
| Message Timeout                              | -     |
| Meter Values Aligned Data                    | 0     |
| Meter Values Aligned Data Max Length         | 8     |
| Meter Values Sampled Data                    | 0     |
| Meter Values Sampled Data Max Length         | 8     |
| MeterValueSampleInterval                     | 30    |
| MinimumStatusDuration                        | 180   |
| Number Of Connectors                         | 1     |
| ResetRetries                                 | 0     |
| StopTransactionMaxMeterValues                | 8     |
| StopTransactionOnEVSideDisconnect            | TRUE  |
| StopTransactionOnInvalidId                   | FALSE |
| StopTxnAlignedData                           | 0     |
| Stop Txn Aligned Data Max Length             | 128   |
| StopTxnSampledData                           | 0     |
| StopTxnSampledDataMaxLength                  | 128   |
| SupportedFeatureProfiles                     | Core  |
| SupportedFeatureProfilesMaxLength            | 1     |
| Transaction Message Attempts                 | 0     |
| Transaction Message Retry Interval           | 20    |
| UnlockConnectorOnEVSideDisconnect            | FALSE |
| WebSocketPingInterval                        | 180   |
| Local Auth List Enabled                      | -     |
| LocalAuthListMaxLength                       | -     |
| SendLocalListMaxLength                       | -     |
| ReserveConnectorZeroSupported                | -     |
| Charge Profile Max Stack Level               | -     |
| Charging Schedule Allowed Charging Rate Unit | -     |
| Charging Schedule Max Periods                | -     |
| ConnectorSwitch3to1PhaseSupported            | -     |
| MaxCharging Profiles Installed               | -     |
| SupportedFileTransferProtocols               | -     |
|  |       |

Page 3 from 4



### Statement of Approval

| Vendor     |                  | <b>Date</b> : 2022.05.02 |
|------------|------------------|--------------------------|
| Name       | Seungryoung Choi | Signature                |
| Company    | Samsung EVC      | 1.0                      |
| Department | Operation Team   | 7 40 47                  |
| Position   | CEO              |                          |
| Location   | Gwangju, Korea   | 2                        |

| Test laboratory |                              | <b>Date</b> : 2022.05.02 |
|-----------------|------------------------------|--------------------------|
| Name            | Philip YANG                  | Signature                |
| Company         | Korea Smart Grid Association | 14                       |
| Department      | Quality Certification Center |                          |
| Position        | Senior Researcher            |                          |
| Location        | Seoul, Korea                 |                          |