# OCPP 1.6 Subset Certificate



Certificate holder: HiEV Charger

Certificate number: OCA.0016.0563.CS

Product type: Charging Station

Product designation: EVW007SK-SV

OCPP Software version: 1.01

Hardware feature set as stated below

Certification date: November 14, 2023

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol covered by this certificate can be found in the abstract of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association, November 14, 2023	(KSGA)HiEV Charger_Test Report template_EVW007SK-SV_231113

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON
Chairman



# **Abstract of test report**

Test Result Summary

Test laboratory:	Korea Smart Grid Association		
Location:	Seoul, Korea		
Test execution location:	KSGA Test Lab		
Test Report Reference:	KSGA-OCPP1.6TEST-207-2023		
Vendor name:	HiEV Charger		
Device Under Test:	Charging Stati	on	
Communication:	JSON		
OCPP Software version:	1,01		
Product designation:	EVW007SK-SV	<i>'</i>	
Test Result Summary	for the ce	ertified functionalities	
Functionalities	OCPP 1.6	Description	
	Certification	•	
	Test Results		
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.	
Optional features			
Firmware Management	N/A	Support for (remote) firmware update management and diagnostic log file download.	
Smart Charging	N/A	Support for Smart Charging (all profile types, including stacking), to control charging.	
Reservation	N/A	Support for reservation of a connector of a Charging Station.	
Local Authorization List Management	N/A	Features to manage a local list in the charging station containing authorization data for whitelisting users.	
Remote Trigger	N/A	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from	

Test Report OCPP 1.6 Certification

Page 1 from 4

the Charging Station.



#### Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	60s	00:00:11	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	60s	00:00:01	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	60s	00:00:00	The response time for the RemoteStartTransaction message.

## Test Configuration

Vendor	HiEV Charger
DUT / SUT	Charging Station
Communication	JSON
Туре	EVW007SK-SV
OCPP Software version	1,01
OCTT version	OCTT 1.6 v1.4.3

Hardware feature set			
Feature Configuration			
Socket(s) / connector(s)	Single		
Fixed cable	<yes></yes>		
Communication technology	Ethernet		
RFID readers	Single		

Non-OCPP Charge Point Configuration		
Configuration key	Value	
<>	<>	

All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:

Limit / setting

Device supports sending milliseconds in timestamps.

Yes



Cardiaatian lan	Malua
Configuration key	Value
AllowOfflineTxForUnknownId AuthorizationCacheEnabled	FALSE
	-
AuthorizeRemoteTxRequests	TRUE
BlinkRepeat	-
ClockAlignedDataInterval	0
ConnectionTimeOut	60
ConnectorPhaseRotation	NotApplicable
ConnectorPhaseRotationMaxLength	-
GetConfigurationMaxKeys	21
HeartbeatInterval	20
LightIntensity	-
LocalAuthorizeOffline	TRUE
LocalPreAuthorize	FALSE
MaxEnergyOnInvalidId	-
MessageTimeout	-
Meter Values Aligned Data	Current.Import, Current.Offered, Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperature, Voltage
MeterValuesAlignedDataMaxLength	-
Meter Values Sampled Data	Current.Import, Current.Offered, Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperature, Voltage
MeterValuesSampledDataMaxLength	voltage
Meter ValueSampleInterval	5
MinimumStatusDuration	5
NumberOfConnectors	
	1
ResetRetries	1
StopTransactionMaxMeterValues	-
StopTransactionOnEVSideDisconnect	TRUE
Stop Transaction On Invalid Id	TRUE
StopTxnAlignedData	Current.Import, Current.Offered, Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperature, Voltage
StopTxnAlignedDataMaxLength	-
StopTxnSampledData	Current.Import, Current.Offered, Energy.Active.Import.Register, Energy.Active.Import.Interval, Power.Offered, SoC, Temperature, Voltage
StopTxnSampledDataMaxLength	-
SupportedFeatureProfiles	Core
SupportedFeatureProfilesMaxLength	-
TransactionMessageAttempts	3
TransactionMessageRetryInterval	30
UnlockConnectorOnEVSideDisconnect	FALSE
WebSocketPingInterval	-
Local Auth List Enabled	-
Local Auth List Max Length	-
Send Local List Max Length	-
ReserveConnectorZeroSupported	-
Charge Profile May Stack Level	
ChargeProfileMaxStackLevel	-
Charging Schedule Allowed Charging Rate Unit	-
Charging Schedule Max Periods	-
Community Construction of the Construction of	_
ConnectorSwitch3to1PhaseSupported	
Connector Switch 3 to 1 Phase Supported  Max Charging Profiles Installed	-

Page 3 from 4



## Statement of Approval

Vendor		Date: 2023.11.14
Name	Dong Ju Kang	Signature
Company	HiEV Charger	
Department	-	G TENEND
Position	CEO	事表加
Location	Pyeongtaek, Korea	

Test laboratory			<b>Date</b> : 2023.11.14
Name	Philip YANG		Signature
Company	Korea Smart Grid Association		١٨
Department	Quality Certification Center		
Position	Chief Researcher		
Location	Seoul, Korea		/