

OCPP 1.6 Subset Certificate



Certificate holder: Pline Motors Co.,Ltd
Certificate number: OCA.0016.0581.CS
Product type: Charging Station
Product designation: NE-R4-01
OCPP Software version: 12D_CE_1.2.00
Hardware feature set as stated below
Certification date: November 22, 2023

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 - Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol covered by this certificate can be found in the abstract of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
<i>Conformance testing according to the test specification referenced by the test report</i>	<i>Korea Smart Grid Association, November 22, 2023</i>	<i>(KSGA)PLINE MOTORS_Test Report_NE-R4-01_v1.5</i>

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON
Chairman

A blue ink signature of Onoph Caron, the Chairman of the Open Charge Alliance.

Abstract of test report

Test Result Summary

Test Report OCPP 1.6 Certification		
Test laboratory:	Korea Smart Grid Association	
Location:	Seoul, Korea	
Test execution location:	Pline Motors Co.,Ltd (Seoul, Korea)	
Test Report Reference:	KSGA-OCPP1.6TEST-212-2023	
Vendor name:	Pline Motors Co.,Ltd	
Device Under Test:	Charging Station	
Communication:	JSON	
OCPP Software version:	12D_CE_1.2.00	
Product designation:	NE-R4-01	
Test Result Summary for the certified functionalities		
Functionalities	OCPP 1.6 Certification Test Results	Description
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.
Optional features		
Firmware Management	N/A	Support for (remote) firmware update management and diagnostic log file download.
Smart Charging	N/A	Support for Smart Charging (all profile types, including stacking), to control charging.
Reservation	N/A	Support for reservation of a connector of a Charging Station.
Local Authorization List Management	N/A	Features to manage a local list in the charging station containing authorization data for whitelisting users.
Remote Trigger	N/A	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.

Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	60s	00:00:22	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	60s	00:00:01	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	60s	00:00:00	The response time for the RemoteStartTransaction message.

Test Configuration

Vendor	Pline Motors Co.,Ltd
DUT / SUT	Charging Station
Communication	JSON
Type	NE-R4-01
OCPP Software version	12D_CE_1.2.00
OCTT version	OCTT 1.6 v1.4.3

Hardware feature set

Feature	Configuration
Socket(s) / connector(s)	Multiple
Fixed cable	<Yes>
Communication technology	Ethernet
RFID readers	Single

Non-OCPP Charge Point Configuration


Configuration key	Value
<>	<>


All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:

Limit / setting	Value
Device supports sending milliseconds in timestamps.	Yes

OCPP Charging Station Configuration	
Configuration key	Value
AllowOfflineTxForUnknownId	-
AuthorizationCacheEnabled	-
AuthorizeRemoteTxRequests	TRUE
BlinkRepeat	-
ClockAlignedDataInterval	0
ConnectionTimeOut	30
ConnectorPhaseRotation	Unknown
ConnectorPhaseRotationMaxLength	-
GetConfigurationMaxKeys	20
HeartbeatInterval	20
LightIntensity	-
LocalAuthorizeOffline	TRUE
LocalPreAuthorize	TRUE
MaxEnergyOnInvalidId	-
MessageTimeout	-
MeterValuesAlignedData	-
MeterValuesAlignedDataMaxLength	12
MeterValuesSampledData	-
MeterValuesSampledDataMaxLength	12
MeterValueSampleInterval	15
MinimumStatusDuration	-
NumberOfConnectors	2
ResetRetries	3
StopTransactionMaxMeterValues	99999999.999
StopTransactionOnEVSideDisconnect	TRUE
StopTransactionOnInvalidId	TRUE
StopTxnAlignedData	-
StopTxnAlignedDataMaxLength	12
StopTxnSampledData	-
StopTxnSampledDataMaxLength	12
SupportedFeatureProfiles	Core
SupportedFeatureProfilesMaxLength	-
TransactionMessageAttempts	1
TransactionMessageRetryInterval	30
UnlockConnectorOnEVSideDisconnect	FALSE
WebSocketPingInterval	60
LocalAuthListEnabled	-
LocalAuthListMaxLength	-
SendLocalListMaxLength	-
ReserveConnectorZeroSupported	-
ChargeProfileMaxStackLevel	-
ChargingScheduleAllowedChargingRateUnit	-
ChargingScheduleMaxPeriods	-
ConnectorSwitch3to1PhaseSupported	-
MaxChargingProfilesInstalled	-
SupportedFileTransferProtocols	-

Statement of Approval

Vendor		Date: 2023.11.22
Name	Hobum Hong	
Company	Pline Motors Co.,Ltd	
Department	Quality Assurance Team	
Position	Team Manager	
Location	Seoul, Korea	

Test laboratory		Date: 2023.11.22
Name	Philip YANG	
Company	Korea Smart Grid Association	
Department	Quality Certification Center	
Position	Chief Researcher	
Location	Seoul, Korea	