OCPP 1.6 Subset Certificate



Certificate holder: BOTARI ENERGY Co., Ltd

Certificate number: OCA.0016.0595.CS

Product type: Charging Station

Product designation: EVon50-30P-1CR-L

OCPP Software version: 02.01.01

Hardware feature set as stated below

Certification date: December 4, 2023

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol covered by this certificate can be found in the abstract of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association, December 4, 2023	(KSGA)BOTARI_Test Report_Evon50- 30P-1CR-L_v1.5

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON Chairman



Abstract of test report

Test Result Summary

Test Report OCPP 1.6 Certification				
Test laboratory:	Korea Smart Grid Association			
Location:	Seoul, Korea			
Test execution location:	KSGA Test Lab			
Test Report Reference:	KSGA-OCPP1.6TEST-222-2023			
Vendor name:	BOTARI ENERGY Co.,Ltd			
Device Under Test:	Charging Station			
Communication:	JSON			
OCPP Software version:	02.01.01			
Product designation:	EVon50-30P-1CR-L			

Test Result Summary for the certified functionalities				
Functionalities	OCPP 1.6 Certification Test Results			
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.		
Optional features				
Firmware Management	N/A	Support for (remote) firmware update management and diagnostic log file download.		
Smart Charging	N/A	Support for Smart Charging (all profile types, including stacking), to control charging.		
Reservation	N/A	Support for reservation of a connector of a Charging Station.		
Local Authorization List Manageme	N/A	Features to manage a local list in the charging station containing authorization data for whitelisting users.		
Remote Trigger	N/A	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.		

Page 1 from 4



Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	60s	00:00:18	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	10s	00:00:03	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	10s	00:00:03	The response time for the RemoteStartTransaction message.

Test Configuration

Vendor	BOTARI ENERGY Co.,Ltd			
DUT / SUT	Charging Station			
Communication	JSON			
Туре	Evon50-30P-1CR-L			
OCPP Software version	02.01.01			
OCTT version	OCTT 1.6 v1.4.3			

Hardware feature set			
Feature Configuration			
Socket(s) / connector(s)	Single		
Fixed cable	<yes></yes>		
Communication technology	Ethernet, Mobile network		
RFID readers	Single		

Non-OCPP Charge Point Configuration		
Configuration key		Value
<>		<>

All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:

Limit / setting	Value
Device supports sending milliseconds in	Yes
timestamps.	res



Configuration key	Value
Configuration key AllowOfflineTxForUnknownId	value
AuthorizationCacheEnabled	
	-
AuthorizeRemoteTxRequests	TRUE
BlinkRepeat	-
ClockAlignedDataInterval	30
ConnectionTimeOut	30
ConnectorPhaseRotation	NotApplicable
ConnectorPhaseRotationMaxLength	-
GetConfigurationMaxKeys	20
HeartbeatInterval	60
LightIntensity	-
LocalAuthorizeOffline	FALSE
LocalPreAuthorize	TRUE
MaxEnergyOnInvalidId	-
MessageTimeout	-
	Current.Import,Current.Offered,Energy
MeterValuesAlignedData	.Active.Import.Register,SoC,Temperat
	ure,Voltage
MeterValuesAlignedDataMaxLength	5
	Current.Import,Current.Offered,Energy
MeterValuesSampledData	.Active.Import.Register,SoC,Temperat
•	ure,Voltage
MeterValuesSampledDataMaxLength	5
MeterValueSampleInterval	20
MinimumStatusDuration	-
NumberOfConnectors	1
ResetRetries	1
StopTransactionMaxMeterValues	
StopTransactionOnEVSideDisconnect	TRUE
StopTransactionOnInvalidId	FALSE
Stophansactionomination	Current.Import,Current.Offered,Energy
StopTxnAlignedData	.Active.Import.Register,SoC,Temperat
StopTxTiAlignedData	
StopTxnAlignedDataMaxLength	ure,Voltage 5
StopTxTIAlignedDataWaxLerigtT	Current.Import,Current.Offered,Energy
StopTxnSampledData	.Active.Import.Register,SoC,Temperat
StopTxTISaTTpleuData	ure,Voltage
StopTxnSampledDataMaxLength	ure, voltage 5
SupportedFeatureProfiles	
SupportedFeatureProfilesMaxLength	Core
TransactionMessageAttempts	
J 1	5
TransactionMessageRetryInterval	60
UnlockConnectorOnEVSideDisconnect	FALSE
WebSocketPingInterval	60
	-
LocalAuthListEnabled	
	-
Local Auth List Max Length	-
Local Auth List Max Length Send Local List Max Length	
Local AuthList Max Length	-
Local Auth List Max Length Send Local List Max Length	
Local Auth List Max Length Send Local List Max Length Reserve Connector Zero Supported	
Local Auth List Max Length Send Local List Max Length Reserve Connector Zero Supported Charge Profile Max Stack Level	-
Local Auth List Max Length Send Local List Max Length Reserve Connector Zero Supported Charge Profile Max Stack Level Charging Schedule Allowed Charging Rate Unit	-
LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods	- - - -
LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods ConnectorSwitch3to1PhaseSupported	- - - - -



Statement of Approval

Vendor		Date: 2023.12.04
Name	Hongsam KIM	Signature
Company	BOTARI ENERGY CO.,Ltd.	
Department	Smart Solution Business Dept	0203
Position	Chief Excutive Officer	
Location	Jeju, Korea	

Test laboratory		Date: 2023.12.04
Name	Philip YANG	Signature
Company	Korea Smart Grid Association	4
Department	Quality Certification Center	
Position	Chief Researcher	
Location	Seoul, Korea	/