OCPP 1.6 Subset Certificate



Certificate holder:	Eaton Corporation
Certificate number:	OCA.0016.0643.CS
Product type:	Charging Station
Product designation:	Green Motion Building and Fleet AC Level2 Charger (GMEV40CME1B-WC) OCPP Software version: 1.3.7C6 Hardware feature set as stated below
Certification date:	February 27, 2024

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol covered by this certificate can be found in the abstract of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	DNV Energy USA, Inc, February 27, 2024	Test Report Eaton Wi-Fi (10483017- ROC-R-01-C)

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON Chairman



Abstract of test report

Test Result Summary

Test Repor	t OCPP 1.6 (Certification	
Test laboratory:	DNV		
Location:	Rochester, NY, USA		
Test execution location:	Rochester, NY	', USA	
Test Report Reference:	10483017-R0)C-R-01-C	
Vendor name:	Eaton Corpora	ation	
Device Under Test:	Charging Stati	ion	
Communication:	JSON		
OCPP Software version:	1.3.7C6		
Due doubt de ciencetions		Building and Fleet AC Level2 Charger	
Product designation:	(GMEV40CME	EIB-WC)	
Test Result Summar	y for the ce	rtified functionalities	
Functionalities	OCPP 1.6	Description	
	Certification		
	Test Results		
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.	
Optional features			
Firmware Management	Pass	Support for (remote) firmware update management and diagnostic log file download.	
Smart Charging	N/A	Support for Smart Charging (all profile types, including stacking), to control charging.	
Reservation	N/A	Support for reservation of a connector of a Charging Station.	
Local Authorization List Management	Pass	Features to manage a local list in the charging station containing authorization data for whitelisting users.	
Remote Trigger	Pass	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.	





Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	30 seconds	4 seconds	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	300 seconds	16 seconds	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	30 seconds	0 seconds	The response time for the RemoteStartTransaction message.

Test Configuration

Vendor	Eaton Corporation
DUT / SUT	Charge Point
Communication	JSON
Туре	Green Motion Building and Fleet AC Level2 Charger (GMEV40CME1B- WC)
OCPP Software version	1.3.7C6
OCTT version	OCTT 1.6 v1.4.4

Hardware feature set			
Feature	Configuration		
Socket(s) / connector(s)	Single		
Fixed cable	Yes		
Communication technology	WiFi		
RFID readers	Single		
Non-OCPP Charge Point Configuration			
Configuration key Value			
<			

All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:

Limit / setting	Value
Device supports sending milliseconds in timestamps.	Yes

Page 2 from 4



OCPP Charging Station Configuration			
Configuration key	Value		
AllowOfflineTxForUnknownId	TRUE		
AuthorizationCacheEnabled	TRUE		
AuthorizeRemoteTxRequests	TRUE		
BlinkRepeat	<optional></optional>		
ClockAlignedDataInterval	10		
ConnectionTimeOut	60		
ConnectorPhaseRotation	NotApplicable		
ConnectorPhaseRotationMaxLength	<pre><pre>coptional></pre></pre>		
GetConfigurationMaxKeys	57		
HeartbeatInterval	10		
LightIntensity	<pre><pre><pre><pre><pre><pre><pre><pre></pre></pre></pre></pre></pre></pre></pre></pre>		
LocalAuthorizeOffline	TRUE		
LocalPreAuthorize	FALSE		
MaxEnergyOnInvalidId	<optional></optional>		
MessageTimeout	<optional></optional>		
MeterValuesAlignedData	Energy.Active.Import.Register		
MeterValuesAlignedDataMaxLength	<pre>coptional></pre>		
Meter valdes Angried Datamax Length			
	Current.Import,Energy.Active.Impo		
Matar) (alwas Samalad Data	rt.Register,Power.Active.Import,Vo		
MeterValuesSampledData	Itage		
MeterValuesSampledDataMaxLength	<optional></optional>		
MeterValueSampleInterval	10		
MinimumStatusDuration	<optional></optional>		
NumberOfConnectors	1		
ResetRetries	0		
StopTransactionMaxMeterValues	<optional></optional>		
StopTransactionOnEVSideDisconnect	FALSE		
StopTransactionOnInvalidId	TRUE		
StopTxnAlignedData	Energy.Active.Import.Register		
StopTxnAlignedDataMaxLength	<optional></optional>		
StopTxnSampledData	Energy.Active.Import.Register		
StopTxnSampledDataMaxLength	<optional></optional>		
	Core,FirmwareManagement,LocalA		
	uthListManagement,Reservation,S		
SupportedFeatureProfiles	martCharging,RemoteTrigger		
SupportedFeatureProfilesMaxLength	<optional></optional>		
TransactionMessageAttempts	3		
TransactionMessageRetryInterval	30		
UnlockConnectorOnEVSideDisconnect	FALSE		
WebSocketPingInterval	<optional></optional>		
LocalAuthListEnabled	TRUE		
LocalAuthListMaxLength	100		
SendLocalListMaxLength	10		
ReserveConnectorZeroSupported	<optional></optional>		
ChargeProfileMaxStackLevel	1		
ChargingScheduleAllowedChargingRateUnit	Current		
ChargingScheduleMaxPeriods	10		
ConnectorSwitch3to1PhaseSupported	<optional></optional>		
MaxChargingProfilesInstalled	3		
SupportedFileTransferProtocols	<optional></optional>		

Page **3** from **4**



Statement of Approval

Vendor		Date: 2024-02-27
Name	Srikanth Shapur	Signature
Company	Eaton Corporation	1
Department	Assemblies & Residential Solutions (ARS)	1 Ja Ma
Position	EVCI System Architect	Sirkath
Location	Peachtree City, GA, USA	

Test laboratory		Date: 2024-02-27
Name	John Watts	Signature
Company	DNV	
Department	BEST T&CC	
Position	Senior Engineer	lan
Location	Rochester, NY, USA	

Page **4** from **4**