OCPP 1.6 Full Certificate



Certificate holder: KEVIT

Certificate number: OCA.0016.0679.CS

Product type: Charging Station

Product designation: DC200A-01

OCPP Software version: 1.0

Hardware feature set as stated below

Certification date: March 20, 2024

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol are also covered by this certification.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association, March 20, 2024	(KSGA)KEVIT_Test Report_DC200A- 01_v1.5

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON Chairman



Abstract of test report

Test Result Summary

Test Report OCPP 1.6 Certification				
Test laboratory:	Korea Smart Grid Association			
Location:	Seoul, Korea			
Test execution location:	KSGA Test Lab			
Test Report Reference: KSGA-OCPP1.6TEST-042-2024				
Vendor name:	KEVIT			
Device Under Test:	Charging Station			
Communication:	JSON			
OCPP Software version: 1.0				
Product designation:	DC200A-01			

1636	Result	Summar y	101	LITE	CC	runea	Turreti	Onanti	C 3
alities			OCI	DD 1	5	Descript	tion		

Functionalities	OCPP 1.6	Description
	Certification	
	Test Results	
Core	Pass	Basic Charging Station functionality
		for booting, authorization (incl. cache
		if available), configuration,
		transactions, remote control.

Optional features		
Firmware Management	Pass	Support for (remote) firmware update management and diagnostic log file download.
Smart Charging	Pass	Support for Smart Charging (all profile types, including stacking), to control charging.
Reservation	Pass	Support for reservation of a connector of a Charging Station.
Local Authorization List Manageme	Pass	Features to manage a local list in the charging station containing authorization data for whitelisting users.
Remote Trigger	Pass	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.

Page 1 from 4



Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	30s	00:00:23	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	30s	00:00:20	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	10s	00:00:00	The response time for the RemoteStartTransaction message.

Test Configuration

Vendor	KEVIT
DUT / SUT	Charging Station
Communication	JSON
Туре	DC200A-01
OCPP Software version	1.0
OCTT version	OCTT 1.6 v1.4.3

Hardware feature set				
Feature	Configuration			
Socket(s) / connector(s)	Multiple			
Fixed cable	<yes></yes>			
Communication technology	Wifi, Ethernet			
RFID readers	Single			

Non-OCPP Charge Point Configuration			
Configuration key	Value		
<>	<>		

All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:

Limit / setting	Value
Device supports sending milliseconds in	Yes
timestamps.	



Configuration key AllowOfflineTxForUnknownId AuthorizationCacheEnabled AuthorizeRemoteTxRequests TRUE BlinkRepeat ClockAlignedDataInterval ConnectionTimeOut ConnectorPhaseRotation ConnectorPhaseRotation GetConfigurationMaxLength Factor Support
AllowOfflineTxForUnknownId FALSE AuthorizationCacheEnabled FALSE AuthorizeRemoteTxRequests TRUE BlinkRepeat - ClockAlignedDataInterval 0 ConnectionTimeOut 60 ConnectorPhaseRotation 1.RST ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 1 HeartbeatInterval 20 LightIntensity - LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedDataMaxLength 16
AuthorizeRemoteTxRequests BlinkRepeat - ClockAlignedDataInterval 0 ConnectionTimeOut 60 ConnectorPhaseRotation 1.RST ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 1 HeartbeatInterval 20 LightIntensity - LocalAuthorizeOffline FALSE LocalPreAuthorize MaxEnergyOnInvalidId MessageTimeout MeterValuesAlignedData MeterValuesAlignedDataMaxLength 1 - ConnectorPhaseRotationMaxLength - BetConfigurationMaxKeys 1 - ConnectorPhaseRotationMaxLength - ConnectorPhaseRotation - BetConfigurationMaxLength - ConnectorPhaseRotation - ConnectorPhas
BlinkRepeat - ClockAlignedDataInterval 0 ConnectionTimeOut 60 ConnectorPhaseRotation 1.RST ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 1 HeartbeatInterval 20 LightIntensity - LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 16
ClockAlignedDataInterval 0 ConnectionTimeOut 60 ConnectorPhaseRotation 1.RST ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 1 HeartbeatInterval 20 LightIntensity - LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 16
ConnectionTimeOut 60 ConnectorPhaseRotation 1.RST ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 1 HeartbeatInterval 20 LightIntensity - LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 16
ConnectionTimeOut 60 ConnectorPhaseRotation 1.RST ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 1 HeartbeatInterval 20 LightIntensity - LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 16
ConnectorPhaseRotationMaxLength - GetConfigurationMaxKeys 1 HeartbeatInterval 20 LightIntensity - LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData MeterValuesAlignedDataMaxLength 16
GetConfigurationMaxKeys 1 HeartbeatInterval 20 LightIntensity - LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 16
GetConfigurationMaxKeys 1 HeartbeatInterval 20 LightIntensity - LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 16
HeartbeatInterval 20 LightIntensity - LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData MeterValuesAlignedDataMaxLength 16
LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData MeterValuesAlignedDataMaxLength 16
LocalAuthorizeOffline FALSE LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData MeterValuesAlignedDataMaxLength 16
LocalPreAuthorize FALSE MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 16
MaxEnergyOnInvalidId - MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 16
MessageTimeout - MeterValuesAlignedData - MeterValuesAlignedDataMaxLength 16
MeterValuesAlignedData - 16 MeterValuesAlignedDataMaxLength 16
MeterValuesAlignedDataMaxLength 16
MeterValuesSampledData Energy.Active.Import.Register
MeterValuesSampledDataMaxLength 16
MeterValueSampleInterval 30
MinimumStatusDuration -
NumberOfConnectors 2
ResetRetries 3
StopTransactionMaxMeterValues 16
StopTransactionOnEVSideDisconnect TRUE
StopTransactionOnInvalidId TRUE
StopTxnAlignedData Energy.Active.Import.Register
StopTxnAlignedData StopTxnAlignedDataMaxLength 16
StopTxnSampledData Energy.Active.Import.Register
StopTxnSampledDataMaxLength 16
Core, Firmware Management, Local.
SupportedFeatureProfiles uthListManagement,Reservation,
martCharging,RemoteTrigger
SupportedFeatureProfilesMaxLength -
TransactionMessageAttempts 3
TransactionMessageRetryInterval 10
UnlockConnectorOnEVSideDisconnect FALSE
WebSocketPingInterval 60
vvebsockerniginterval 00
LocalAuthListEnabled FALSE
LocalAuthListMaxLength 50
SendLocalListMaxLength 10
ReserveConnectorZeroSupported FALSE
ChargeProfileMaxStackLevel 10
ChargingScheduleAllowedChargingRateUnit Ampère & Watt
ChargingScheduleMaxPeriods 10
ConnectorSwitch3to1PhaseSupported -
MaxChargingProfilesInstalled 10
Supported File Transfer Protocols

Page 3 from 4



Statement of Approval

Vendor		Date : 2024.03.20
Name	JaeSeong Kim	Signature
Company	KEVIT	/
Department	R&D Center	
Position	Junior Researcher	$\langle \rangle$
Location	Seoul, Korea	

Test laboratory		Date: 2024.03.20
Name	Philip YANG	Signature
Company	Korea Smart Grid Association	4
Department	Quality Certification Center	
Position	Chief Researcher	
Location	Seoul, Korea	