OCPP 1.6 Subset Certificate



Certificate holder: EVSIS Co., Ltd.

Certificate number: OCA.0016.0702.CS

Product type: Charging Station

Product designation: JC-9642-240-012

OCPP Software version: 0.0.1

Hardware feature set as stated below

Certification date: April 1, 2024

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol covered by this certificate can be found in the abstract of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association, April 1, 2024	(KSGA)EVSIS_Test Report_JC-9642- 240-012_v1.5

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON



Abstract of test report

Remote Trigger

Test Result Summary

•			
Test laboratory:	Korea Smart Grid Association		
Location:	Seoul, Korea		
Test execution location:	EVSIS Co., Ltd. (Seoul, Korea)		
Test Report Reference:	KSGA-OCPP1	.6TEST-047-2024	
Vendor name:	EVSIS Co., Lt	d.	
Device Under Test:	Charging Stat	tion	
Communication:	JSON		
OCPP Software version:	0.0.1		
Product designation:	JC-9642-240-	012	
Test Result Summary	for the ce	rtified functionalities	
Functionalities	OCPP 1.6	Description	
	Certification		
	Test Results		
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.	
Optional features			
Firmware Management	N/A	Support for (remote) firmware update management and diagnostic log file download.	
Smart Charging	N/A	Support for Smart Charging (all profile types, including stacking), to control charging.	
Reservation	N/A	Support for reservation of a connector of a Charging Station.	
Local Authorization List Manageme	N/A	Features to manage a local list in the charging station containing authorization data for whitelisting	

Test Report OCPP 1.6 Certification

Page 1 from 4

N/A

users.

Station.

Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging



Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	150s	00:02:02	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	30s	00:00:01	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	30s	00:00:00	The response time for the RemoteStartTransaction message.

Test Configuration

Vendor	EVSIS Co., Ltd.
DUT / SUT	Charging Station
Communication	JSON
Туре	JC-9642-240-012
OCPP Software version	0.0.1
OCTT version	OCTT 1.6 v1.4.3

Hardware feature set				
Feature Configuration				
Socket(s) / connector(s)	Multiple			
Fixed cable	<yes></yes>			
Communication technology	Ethernet			
RFID readers	Single			
Non-OCPP Charge Point Configuration				
Configuration key Value				
<>	<>			

All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:		
Limit / setting Value		
Device supports sending milliseconds in timestamps.	Yes	



Configuration key	Value
AllowOfflineTxForUnknownId	TRUE
AuthorizationCacheEnabled	FALSE
AuthorizeRemoteTxRequests	FALSE
BlinkRepeat	-
ClockAlignedDataInterval	180
ConnectionTimeOut	60
ConnectorPhaseRotation	RST
ConnectorPhaseRotationMaxLength	-
GetConfigurationMaxKeys	3
Heartbeatinterval	20
LightIntensity	-
LocalAuthorizeOffline	FALSE
LocalPreAuthorize	FALSE
MaxEnergyOnInvalidId	-
MessageTimeout	_
Meter Values Aligned Data	Energy.Active.Import.Register
Meter Values Aligned Data Max Length	8
	Current.Import, Current.Offered,
	Energy.Active.Import.Register,
Meter Values Sampled Data	Power.Active.Import, Power.Offered
	1 ' '
NAME OF THE OWNER OW	SoC, Voltage
MeterValuesSampledDataMaxLength	8
MeterValueSampleInterval	20
MinimumStatusDuration	-
NumberOfConnectors	2
ResetRetries	3
StopTransactionMaxMeterValues	-
StopTransactionOnEVSideDisconnect	TRUE
Stop Transaction On Invalid Id	TRUE
	Current.Import, Current.Offered,
	Energy.Active.Import.Register,
StopTxnAlignedData	Energy.Active.Import.Interval,
	Power.Active.Import, Power.Offered
	SoC, Voltage
StopTxnAlignedDataMaxLength	8
	Current.Import, Current.Offered,
StopTxnSampledData	Energy.Active.Import.Register,
StopTxITSampleuData	Power.Active.Import, Power.Offered
	SoC, Voltage
StopTxnSampledDataMaxLength	8
SupportedFeatureProfiles	Core
SupportedFeatureProfilesMaxLength	6
TransactionMessageAttempts	2
TransactionMessageRetryInterval	30
UnlockConnectorOnEVSideDisconnect	FALSE
WebSocketPingInterval	0
1 la . #L1 :- #F L1 - d	
LocalAuthListEnabled	-
LocalAuthListMaxLength	-
SendLocalListMaxLength	-
ReserveConnectorZeroSupported	-
ChargeProfileMaxStackLevel	-
ChargingScheduleAllowedChargingRateUnit	-
ChargingScheduleMaxPeriods	-
	+
ConnectorSwitch3to1PhaseSupported	-
ConnectorSwitch3to1PhaseSupported MaxChargingProfilesInstalled	-
Connector Switch 3 to 1 Phase Supported Max Charging Profiles Installed Supported File Transfer Protocols	-

Page 3 from 4



Statement of Approval

Vendor		Date: 2024.04.01
Name	Kyung-Jin Ko	Signature
Company	EVSIS Co., Ltd.	
Department	Software convergence team	L/
Position	Researcher	
Location	Seoul, Korea	•

Test laboratory		Date: 2024.04.01
Name	Philip YANG	Signature
Company	Korea Smart Grid Association	L
Department	Quality Certification Center	
Position	Chief Researcher	
Location	Seoul, Korea	