# OCPP 1.6 Full Certificate



Certificate holder: EVSIS Co., Ltd.

Certificate number: OCA.0016.0775.CS

**Product type:** Charging Station

Product designation: JC-91B2-14-0O4

OCPP Software version: 0.0.1

Hardware feature set as stated below

Certification date: May 23, 2024

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol are also covered by this certification.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Testing Certification institute, May 23, 2024	(KSGA)EVSIS_Test Report_JC-91B2- 14-004_v1.5

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON Chairman



# **Abstract of test report**

Functionalities

### Test Result Summary

Test laboratory:	Korea Smart Grid Association
Location:	Seoul, Korea
Test execution location:	EVSIS Co., Ltd. (Seoul, Korea)
Test Report Reference:	KSGA-OCPP1.6TEST-073-2024
endor name:	EVSIS Co., Ltd.
evice Under Test:	Charging Station
ommunication:	JSON
CPP Software version:	0.0.1
Product designation:	JC-91B2-14-004

### Test Result Summary for the certified functionalities

OCPP 1.6 Description

T direction director	OCH III	Description
	Certification	
	Test Results	
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.
Optional features		
Firmware Management	Pass	Support for (remote) firmware update management and diagnostic log file download.
Smart Charging	Pass	Support for Smart Charging (all profile types, including stacking), to control charging.
Reservation	Pass	Support for reservation of a connector of a Charging Station.
Local Authorization List Manageme	Pass	Features to manage a local list in the charging station containing authorization data for whitelisting users.
Remote Trigger	Pass	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.

Page 1 from 4



### Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	90s	00:01:01	The response time for when waiting for an OCPP function with its corresponding request message.  (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	30s	00:00:01	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	30s	00:00:01	The response time for the RemoteStartTransaction message.

### **Test Configuration**

Vendor	EVSIS Co., Ltd.
DUT / SUT	Charging Station
Communication	JSON
Туре	JC-91B2-14-0O4
OCPP Software version	0.0.1
OCTT version	OCTT 1.6 v1.4.3

Hardware feature set				
Feature Configuration				
Socket(s) / connector(s)	Multiple			
Fixed cable	<yes></yes>			
Communication technology	Ethernet			
RFID readers	Single			

Non-OCPP Charge Point Configuration			
Configuration key		Value	
<>		<>	



Configuration key	Value
AllowOfflineTxForUnknownId	FALSE
AuthorizationCacheEnabled	FALSE
AuthorizeRemoteTxRequests	FALSE
BlinkRepeat	-
ClockAlignedDataInterval	0
ConnectionTimeOut	60
ConnectorPhaseRotation	RST
ConnectorPhaseRotationMaxLength	10
GetConfigurationMaxKeys	11
HeartbeatInterval	20
LightIntensity	-
LocalAuthorizeOffline	TRUE
LocalPreAuthorize	TRUE
MaxEnergyOnInvalidId	-
MessageTimeout	-
MessageTimeout	Current Import Current Offered
	Current.Import, Current.Offered,
Material Column Aliana d Data	Energy.Active.Import.Register, Energy.Active.Import.Interval,
MeterValuesAlignedData	
	Power.Active.Import, Power.Offered SoC, Voltage
Makadah arakh	
MeterValuesAlignedDataMaxLength	8
	Current.Offered, Voltage,
MeterValuesSampledData	Energy.Active.Import.Register,
·	Power.Offered,Current.Import,Powe
	.Active.Import
Meter Values Sampled Data Max Length	8
Meter Value Sample Interval	300
MinimumStatusDuration	-
NumberOfConnectors	2
ResetRetries	3
StopTransactionMaxMeterValues	-
StopTransactionOnEVSideDisconnect	TRUE
StopTransactionOnInvalidId	TRUE
	Current.Import, Current.Offered,
	Energy.Active.Import.Register,
StopTxnAlignedData	Energy.Active.Import.Interval,
	Power.Active.Import, Power.Offered
	SoC, Voltage
StopTxnAlignedDataMaxLength	8
	Current.Import, Current.Offered,
StopTxnSampledData	Energy.Active.Import.Register,
stoptxisampledbata	Power.Active.Import, Power.Offered
	Voltage
StopTxnSampledDataMaxLength	8
- · · · ·	Core,FirmwareManagement,LocalA
SupportedFeatureProfiles	thListManagement,Reservation,Sm
**	rtCharging,RemoteTrigger
SupportedFeatureProfilesMaxLength	6
Supported Feature Profiles Max Length Transaction Message Attempts	
Transaction Message Attempts	6
Transaction Message Attempts Transaction Message Retry Interval	6 3 30
Transaction Message Attempts Transaction Message RetryInterval Unlock Connector On EV Side Disconnect	6 3
Transaction Message Attempts Transaction Message RetryInterval Unlock Connector On EV Side Disconnect Web Socket PingInterval	6 3 30 FALSE 300
Transaction Message Attempts Transaction Message RetryInterval Unlock Connector On EV Side Disconnect Web Socket PingInterval Local Auth List Enabled	6 3 30 FALSE 300 FALSE
Transaction Message Attempts Transaction Message RetryInterval Unlock Connector On EV Side Disconnect Web Socket Ping Interval Local Auth List Enabled Local Auth List Max Length	6 3 30 FALSE 300 FALSE 100000
Transaction Message Attempts Transaction Message RetryInterval Unlock Connector On EV Side Disconnect Web Socket Ping Interval Local Auth List Enabled Local Auth List Max Length Send Local List Max Length	6 3 30 FALSE 300 FALSE 100000 100
Transaction Message Attempts Transaction Message RetryInterval Unlock Connector On EV Side Disconnect Web Socket Ping Interval Local Auth List Enabled Local Auth List Max Length	6 3 30 FALSE 300 FALSE 100000
Transaction Message Attempts Transaction Message RetryInterval Unlock Connector On EV Side Disconnect Web Socket PingInterval Local Auth List Enabled Local Auth List Max Length Send Local List Max Length Reserve Connector Zero Supported	6 3 30 FALSE 300 FALSE 100000 100
Transaction Message Attempts Transaction Message RetryInterval Unlock Connector On EV Side Disconnect Web Socket PingInterval Local Auth List Enabled Local Auth List Max Length Send Local List Max Length Reserve Connector Zero Supported Charge Profile Max Stack Level	6 3 30 FALSE 300 FALSE 100000 100 FALSE
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit	6 3 30 FALSE 300 FALSE 100000 100 FALSE 5 Ampère
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods	6 3 30 FALSE 300 FALSE 100000 100 FALSE 5 Ampère 24
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods ConnectorSwitch3to1PhaseSupported	6 3 30 FALSE 300 FALSE 100000 100 FALSE 5 Ampère 24 FALSE
TransactionMessageAttempts TransactionMessageRetryInterval UnlockConnectorOnEVSideDisconnect WebSocketPingInterval LocalAuthListEnabled LocalAuthListMaxLength SendLocalListMaxLength ReserveConnectorZeroSupported ChargeProfileMaxStackLevel ChargingScheduleAllowedChargingRateUnit ChargingScheduleMaxPeriods	6 3 30 FALSE 300 FALSE 100000 100 FALSE 5 Ampère 24

Page 3 from 4



## Statement of Approval

Vendor		Date: 2024.05.23
Name	Kyung-Jin Ko	Signature
Company	EVSIS Co., Ltd.	
Department	Software convergence team	L
Position	Researcher	
Location	Seoul, Korea	,

Test laboratory		Date: 2024.05.23
Name	Philip YANG	Signature
Company	Korea Smart Grid Association	ام
Department	Quality Certification Center	
Position	Chief Researcher	
Location	Seoul, Korea	