OCPP 1.6 Subset Certificate



Certificate holder: Seoul Electronics & Telecom

Certificate number: OCA.0016.0777.CS

Product type: Charging Station

Product designation: EVSP007-1CHB

OCPP Software version: 1.0.0

Hardware feature set as stated below

Certification date: May 28, 2024

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol covered by this certificate can be found in the abstract of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association, May 28, 2024	(KSGA)SET_Test Report_EVSP007- 1CHB_v1.5

The abstract of test report in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON
Chairman



Abstract of test report

Test Result Summary

Test Report OCPP 1.6 Certification				
Korea Smart Grid Association				
Seoul, Korea				
KSGA Test Lab				
KSGA-OCPP1.6TEST-074-2024				
Seoul Electronics & Telecom				
Charging Station				
JSON				
1.0.0				
EVSP007-1CHB				

Test Result Summary for the certified functionalities				
Functionalities	OCPP 1.6	Description		
	Certification			
	Test Results			
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.		
Optional features				
Firmware Management	N/A	Support for (remote) firmware update management and diagnostic log file download.		
Smart Charging	N/A	Support for Smart Charging (all profile types, including stacking), to control charging.		
Reservation	N/A	Support for reservation of a connector of a Charging Station.		
Local Authorization List Manageme	N/A	Features to manage a local list in the charging station containing authorization data for whitelisting users.		
Remote Trigger	N/A	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.		

Page 1 from 4



Performance Measurement Results

Name	PICS value	Measured value	Description
OCPP triggered function timeout:	90s	00:00:02	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)
OCPP response timeout:	5s	00:00:01	The response time for when waiting for an OCPP response message.
Response time RemoteStartTransaction:	5s	00:00:00	The response time for the RemoteStartTransaction message.

Test Configuration

Vendor	Seoul Electronics & Telecom		
DUT / SUT	Charging Station		
Communication	JSON		
Туре	EVSP007-1CHB		
OCPP Software version	1.0.0		
OCTT version	OCTT 1.6 v1.4.3		

Hardware feature set			
Feature	Configuration		
Socket(s) / connector(s)	Single		
Fixed cable	<yes></yes>		
Communication technology	Mobile network		
RFID readers	Single		

Non-OCPP Charge Point Configuration			
Configuration key	Value		
<>	<>		

All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:			
Limit / setting	Value Yes		
Device supports sending milliseconds in			
timestamps.	res		



Configuration key AllowOfflineTxForUnknownId AuthorizationCacheEnabled AuthorizeRemoteTxRequests BlinkRepeat	TRUE FALSE
AuthorizationCacheEnabled AuthorizeRemoteTxRequests BlinkRepeat	
AuthorizeRemoteTxRequests BlinkRepeat	EVICE
BlinkRepeat	
-	TRUE
	-
ClockAlignedDataInterval	0
ConnectionTimeOut	60
ConnectorPhaseRotation	NotApplicable
ConnectorPhaseRotationMaxLength	-
GetConfigurationMaxKeys	20
HeartbeatInterval	20
LightIntensity	-
LocalAuthorizeOffline	FALSE
LocalPreAuthorize	FALSE
MaxEnergyOnInvalidId	-
MessageTimeout	-
MeterValuesAlignedData	Energy, Active, Import, Register
MeterValuesAlignedDataMaxLength	20
MeterValuesSampledData	Energy, Active, Import, Register
MeterValuesSampledDataMaxLength	20
MeterValueSampleInterval	20
MinimumStatusDuration	-
NumberOfConnectors	1
ResetRetries	3
StopTransactionMaxMeterValues	20
StopTransactionOnEVSideDisconnect	TRUE
StopTransactionOnInvalidId	TRUE
StopTxnAlignedData	-
StopTxnAlignedDataMaxLength	20
StopTxnSampledData	-
StopTxnSampledDataMaxLength	20
SupportedFeatureProfiles	Core
SupportedFeatureProfilesMaxLength	-
TransactionMessageAttempts	3
TransactionMessageRetryInterval	10
UnlockConnectorOnEVSideDisconnect	TRUE
WebSocketPingInterval	10
LocalAuthListEnabled	-
LocalAuthListMaxLength	-
SendLocalListMaxLength	-
ReserveConnectorZeroSupported	-
ChargeProfileMaxStackLevel	-
ChargingScheduleAllowedChargingRateUnit	-
ChargingScheduleMaxPeriods	-
ConnectorSwitch3to1PhaseSupported	-
MaxChargingProfilesInstalled	
rianoriaryingi romesii istalleu	

Page 3 from 4



Statement of Approval

Vendor		Date: 2024.05.28	
Name Bae Dong-Ju		Signature	
Company Seoul Electronics & Telecom			
Department	ODM R&D	1472	
Position	Senior Research Engineer	0163	
Location	Incheon, Korea	'	

Test laboratory		Date : 2024.05.28
Name	Philip YANG	Signature
Company	Korea Smart Grid Association	ام
Department Quality Certification Center		
Position	Chief Researcher	
Location	Seoul, Korea	