



Certificate Holder: Lite-On Technology Corp.
Certificate Number: OCA.0201.0045.CS
Product Type: Charging Station
Product Designation: W1-UC168
OCPP Software Version: v01.01
Certification Date: November 19, 2024

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 2.0.1 (Edition 3 FINAL, 2024-05-06 including Errata 2024-09). The optional OCPP protocol features that are covered by this certificate can be found in the Abstract of the Test Report that is part of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in this complete test report.

Applied	Performed by / On	Document Evidence
Conformance testing according to the test specification referenced by the test report	DNV Singapore Pte. Ltd. October 4, 2024	PICS_PRJ_10522960_signed

The abstract of test report is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON
Chairman

Abstract of the Test Report

Test Report OCPP 2.0.1 Certification

Test laboratory:	DNV Singapore Pte. Ltd.
Location:	Singapore
Test Report Reference:	Logfiles_PRJ_10522960
Product Designation:	WI-UC168
Vendor name:	Lite-On Technology Corp.
Device Under Test:	Charging Station
OCPP Software Version	v01.01

Test Result Summary for the Certified Functionalities

Certification Profile	Test Result	Description
Core	Pass	Basic Charging Station functionality for booting, authorization, configuration, transactions, remote control, including basic security.
Advanced Security	Pass	Support for TLS with client authentication.
Local Authorization List Management	Not Tested	Support for local authorization list management and optionally of an authorization cache.
Smart Charging	Not Tested	Support for Smart Charging, to control charging.
Advanced Device Management	Not Tested	Support for the OCPP Device Model and advanced logging and monitoring.
Reservation	Not Tested	Support for reservation of a connector of a Charging Station.
Advanced User Interface	Not Tested	Support for tariff & cost and DisplayMessage functionality.
ISO 15118 Support	Not Tested	Support for ISO 15118 Smart Charging and Plug and Charge authorization.

Hardware Feature Set

ID	Feature	Supported / Present
HFS-1	Has a detachable cable	No
HFS-2	Has a fixed cable	No
HFS-3	Has AC support	Yes
HFS-4	Has DC support	No
HFS-5	Has 1 phase support	Yes
HFS-6	Has 2 phase support	No
HFS-7	Has 3 phase support	No
HFS-8	No. EVSEs	1
HFS-9	Communication technology	WiFi, Ethernet, Mobile network
HFS-10	RFID readers	Single

EVSE	Current	Phases	Connector	Type	Cable Type
1	AC	1	1	cType1	Other

Optional Features

Core

ID	Core Features	Supported / Present
C-01	Support for offline authorization of transactions	Yes
C-02	Support for allowing Offline Authorization for Unknown Ids	Yes
C-03	Support for maximizing energy for invalid ids	Yes
C-04	Support to limit StatusNotifications	No
C-06	Authorization status after cable disconnected on EV side	
C-06.1	Support for maintaining authorization when cable disconnected on EV side	Yes
C-06.2	Support for not maintaining authorization when cable disconnected on EV side	Yes
C-07	Support for using a Master Pass for charging stations with UI	Yes
C-08	Support for using a Master Pass for charging stations without UI	No
C-09	Supported Transaction Start points	
C-09.1	Start transaction options - EVConnected	Yes

ID	Core Features	Supported / Present
C-09.2	Start transaction options - Authorized	No
C-09.3	Start transaction options - DataSigned	No
C-09.4	Start transaction options - PowerPathClosed	Yes
C-09.5	Start transaction options - EnergyTransfer	No
C-09.6	Start transaction options - ParkingBayOccupancy	No
C-10	Supported Transaction Stop points	
C-10.1	Stop transaction options - EVConnected	Yes
C-10.2	Stop transaction options - Authorized	No
C-10.3	Stop transaction options - PowerPathClosed	Yes
C-10.4	Stop transaction options - EnergyTransfer	No
C-10.5	Stop transaction options - ParkingBayOccupancy	No
C-12	Unlocking of connector when cable disconnected on EV side	
C-12.1	Support for unlocking connector when cable disconnected on EV side	Yes
C-12.2	Support for not unlocking when cable disconnected on EV side	No
C-13	Support for Reset per EVSE	Yes
C-14	Support for retrieving / deleting CustomerInformation - CustomerIdentifier	No
C-20	Allowing New Sessions Pending a FirmwareUpdate	No
C-21	Support for queuing all or only Transaction related messages until they are delivered to the CSMS	No
C-23	Supported time sources	Heartbeat NTP RealTimeClock
C-25	Support for setting a TimeOffset	Yes
C-26	Support for setting the TimeZone	No
C-28	Toggle sending clock aligned meter values when a transaction is ongoing / Idle	Yes
C-29	TriggerMessage	
C-29.1	Trigger message - MeterValues	Yes
C-29.2	Trigger message - TransactionEvent	Yes
C-29.3	Trigger message - LogStatusNotification	Yes
C-29.4	Trigger message - FirmwareStatusNotification	Yes
C-29.5	Trigger message - StatusNotification	Yes
C-29.6	Trigger message - BootNotification	Yes

ID	Authorization Options for Local Start	Tested During Certification
C-30	Authorization - using RFID ISO14443	Yes
C-31	Authorization - using RFID ISO15693	No
C-32	Authorization - using KeyCode	No
C-33	Authorization - using locally generated id	No
C-34	Authorization - MacAddress	No
C-35	Authorization - NoAuthorization	No

ID	Authorization Options for Remote Start	Tested During Certification
C-36	Authorization - using RFID ISO14443	Yes
C-37	Authorization - using RFID ISO15693	No
C-38	Authorization - using centrally, in the CSMS generated id	No
C-39	Authorization - NoAuthorization	No

ID	Metervalues	Tested During Certification	Supported According to Vendor
C-40	Supported MeterValue Measurands		
C-40.1	SampledTxBegan Measurands	Current.Offered Power.Offered Current.Import Energy.Active.Import.Register Power.Active.Import Voltage	Current.Import Current.Offered Energy.Active.Import.Register Energy.Active.Import.Interval Power.Active.Import Power.Offered Voltage
C-40.2	SampledTxUpdated Measurands	Current.Offered Power.Offered Current.Import Energy.Active.Import.Register Power.Active.Import Voltage	Current.Import Current.Offered Energy.Active.Import.Register Energy.Active.Import.Interval Power.Active.Import Power.Offered Voltage
C-40.3	SampledTxEnded Measurands	Energy.Active.Import.Register	Current.Import Current.Offered Energy.Active.Import.Register Energy.Active.Import.Interval Power.Active.Import Power.Offered Voltage

ID	Metervalues	Tested During Certification	Supported According to Vendor
C-40.4	AlignedData Measurands	Current.Offered Energy.Active.Import.Interval Power.Offered Current.Import Energy.Active.Import.Register Power.Active.Import Voltage	Current.Import Current.Offered Energy.Active.Import.Register Energy.Active.Import.Interval Power.Active.Import Power.Offered Voltage
C-40.5	AlignedDataTxEnded Measurands	Current.Offered Energy.Active.Import.Interval Power.Offered Current.Import Energy.Active.Import.Register Power.Active.Import Voltage	Current.Import Current.Offered Energy.Active.Import.Register Energy.Active.Import.Interval Power.Active.Import Power.Offered Voltage

ID	Cipher Suites	Supported / Present
C-41	Supported Cipher Suites	TLS_RSA_WITH_AES_128_GCM_SHA256 TLS_RSA_WITH_AES_256_GCM_SHA384

ID	Core Features	Supported / Present
C-42	Signed Metervalues	No
C-43	Install and activate Firmware with ongoing transaction	No
C-47	Support for falling back to default OCPP reconnection mechanism when NetworkConnection profile connection has failed	Yes
C-48	Authorization of remote start	
C-48.1	Option for authorization in case of a remote start	Yes
C-48.2	Option for no authorization in case of a remote start	Yes
C-58	Option for disabling remote authorization	Yes
C-49	Authorization Cache	Yes
C-59	Option for disabling remote authorization for cached invalid idTokens	Yes
C-51	Configurable TxStartPoint	Yes
C-52	Configurable TxStopPoint	Yes
C-53	Support for lifetime cached token	Yes
C-54	Supported policies for replacing cached entries	No
C-56	Support for providing the SummaryInventory	Yes

ID	Core Features	Supported / Present
C-57	Support for cancelling ongoing log file upload	No
C-60	Support for cancelling ongoing firmware update	Yes

Advanced Security

ID	Certification Profile: Advanced Security	Supported / Present
AS-2	Additional root certificate check mechanism implemented	No
AS-3	Update Charging Station Certificate - CertificateSignedRequest Timeout	Yes

Additional Questions

ID	Additional Questions for Lab Testing	Supported / Present
AQ-1	Can the last CSMSRootCertificate can be removed?	No
AQ-2	Does the Charging Station have a cable lock, which prevents the EV driver to connect the EV and EVSE before authorization?	No
AQ-3	Can the last ChargingStationCertificate be removed?	Yes
AQ-4	Is there at least one unsupported NumberOfPhases?	No
AQ-5	Does the Charging Station have at least one hardWired monitor?	No
AQ-6	Does the Charging Station have a pre-configured monitor?	No
AQ-7	Is your Charging Station able to download firmware while there is an ongoing transaction?	No
AQ-8	Does your Charging Station enforce a selection of EVSE prior to authorization?	No
AQ-9	Does your Charging Station support charging an EV using IEC 61851-1?	Yes

Other Relevant Settings

ID	Limit / Setting	Value
ORS-1	ItemsPerMessageGetReport	10
ORS-2	ItemsPerMessageGetVariables	10
ORS-3	ItemsPerMessageSetVariables	10
ORS-4	BytesPerMessageGetReport	1024
ORS-5	BytesPerMessageGetVariables	10240
ORS-6	BytesPerMessageSetVariables	10240
ORS-7	Minimum MessageAttemptIntervalTransactionEvent supported	1
ORS-8	Maximum MessageAttemptIntervalTransactionEvent supported	60
ORS-9	Minimum SampledDataTxUpdatedInterval supported	0
ORS-10	Maximum SampledDataTxUpdatedInterval supported	86400
ORS-11	Minimum HeartbeatInterval supported	0
ORS-12	Maximum HeartbeatInterval supported	86400
ORS-14	Minimum WebSocketPingInterval supported	0
ORS-15	Maximum WebSocketPingInterval supported	86400
ORS-16	WebSocketPingInterval	120

ID	Security Related Settings	Value
ORS-17	CertificateEntries	10
ORS-18	MaxCertificateChainSize	10000

ID	Firmware Management Settings	Value
ORS-24	Supported file transfer protocols	http, https, ftp, sftp, ftps


Performance Measurement Result

Name	Max Value	Unit	Description
OCPP response time	20	seconds	The response time for when waiting for an OCPP response message after sending an OCPP request message. This entails all OCPP messages. Messages to the DUT can be handled within this timeout.
OCPP triggered function response time	20	seconds	The response time used when waiting for an asynchronous OCPP report after requesting this report.
Transaction authorization time by RequestStartTransactionRequest	20	seconds	The time between a RequestStartTransactionRequest and the corresponding TransactionEventRequest. Only cases where the RequestStartTransactionRequest immediately results in an authorization followed by a TransactionEventRequest, without the need of any additional manual actions or chargingState transitions inbetween are included.
Transaction authorization end time by RequestStopTransactionRequest	20	seconds	The time between a RequestStopTransactionRequest and the corresponding TransactionEventRequest. Only cases where the RequestStopTransactionRequest immediately results in an end of the authorization followed by a TransactionEventRequest, that do not contain transactionInfo.chargingState = EVConnected are included.

Name	Min Value	Max Value	Average Value	Unit
OCPP response time	0.24	7.33	0.58	seconds
OCPP triggered function response time	0.53	13.34	4.11	seconds
Transaction authorization time by RequestStartTransactionRequest	1.33	2.04	1.68	seconds
Transaction authorization end time by RequestStopTransactionRequest	not measurable	not measurable	not measurable	seconds

Communication technology used during performance measurement:	WiFi
---	------

Statement of Approval

Vendor		
Name	Roy RC Chen	Date: 2024-11-19
Company	Lite-On Technology Corp.	Signature:
Department	Safety	
Position	Safety Principal Engineer	
Location	Taiwan	

Test Laboratory		
Name	Liu Xinyang	Date: 2024-11-19
Company	DNV Singapore Pte. Ltd.	Signature:
Department	Energy Systems	
Position	Consultant	
Location	Singapore	