

Certificate Holder: Certificate Number: Product Type: Product Designation: OCPP Software Version: Certification Date: MOTREX EV OCA.0016.0941.CS Charging Station CR-S7KS-V2-PLC V2.0.1 November 8, 2024

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 (Edition 2 FINAL, 2017-09-28 including Errata v4.0 Release, 2019-10-23). The optional OCPP protocol features that are covered by this certificate can be found in the Abstract of the Test Report that is part of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in this complete test report.

Applied	Performed by / On	Document Evidence
Conformance testing according to the test specification referenced by the test report		OCPP_PICS 1.6 CS_CR-S7KS-V2-PLC_v1.1. 7

The abstract of test report is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON Chairman



Abstract of the Test Report

Test Report OCPP 1.6 Certification

Test laboratory:	Korea Smart Grid Association
Location:	Seoul, Korea
Test Report Reference:	KSGA-OCPP1.6TEST-162-2024
Test Location	KSGA Test Lab
Product Designation:	CR-S7KS-V2-PLC
Vendor name:	MOTREX EV
Device Under Test:	Charging Station
OCPP Software Version	V2.0.1

Test Result Summary for the Certified Functionalities

Certification Profile	Test Result	Description
Core	Pass	Basic Charging Station, functionality for booting, authorization, configuration, transactions, remote control.
Firmware Management	Pass	Support for firmware update management and diagnostic log file download.
Local Authorization List Management	Not Tested	Features to manage a local list in the charging station containing authorization data for whitelisting users.
Smart Charging	Not Tested	Support for Smart Charging, to control charging.
Remote Trigger	Pass	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.
Reservation	Not Tested	Support for reservation of a connector of a Charging Station.



Hardware Feature Set

ID	Feature	Supported / Present
HFS-1	Has a detachable cable	No
HFS-2	Has a fixed cable	Yes
HFS-3	Has AC support	Yes
HFS-4	Has DC support	No
HFS-5	Has 1 phase support	Yes
HFS-6	Has 2 phase support	No
HFS-7	Has 3 phase support	No
HFS-8	No. Connectors	1
HFS-9	Communication technology	Mobile Network
HFS-10	RFID readers	Single

Connector	Current	Phases	Туре	Cable Type
1	AC	1	cType1	Fixed Cable

Optional Features

Core	

ID	Core Features	Supported / Present
C-01	Support for offline authorization of transactions	Yes
C-02	Support for allowing Offline Authorization for Unknown Ids	Yes
C-03	Support for maximizing energy for invalid ids	No
C-04	Authorization Cache	Yes
C-05	Support to limit StatusNotifications	Yes
C-06	Authorization status after cable disconnected on EV side	
C-06.1	Support for maintaining authorization when cable disconnected on EV side	No
C-06.2	Support for not maintaining authorization when cable disconnected on EV side	Yes
C-07	Support for local start	Yes
C-08	Support for local stop	Yes



ID	Metervalues	Tested During Certification	Supported According to Vendor
C-09	Supported MeterValue Measurands		
C-09.1	MeterValuesSampledData	Voltage Current.Import Energy.Active.Import.Register Power.Active.Import	Energy.Active.Import.Register Power.Active.Import Current.Import Voltage
C-09.2	MeterValuesAlignedData	Energy.Active.Import.Register	Energy.Active.Import.Register

Firmware Management

ID	Certification Profile: Firmware Management	Supported / Present
F-1	Support for Secure Firmware Updates	False

Additional Questions

ID	Additional Questions for Lab Testing	Supported / Present
AQ-1	Can the last CentralSystemRootCertificate can be removed?	No
AQ-2	Does the Charging Station have a cable lock, which prevents the EV driver to connect the EV and EVSE before authorization?	No
AQ-3	Can the last ChargePointCertificate be removed?	No
AQ-4	Is your Charging Station able to download firmware while there is an ongoing transaction?	No
AQ-5	Does your Charging Station enforce a selection of EVSE prior to authorization?	No
AQ-6	Does your Charging Station support charging an EV using IEC 61851-1?	No
AQ-7	Reporting of StopTransaction after power loss	
AQ-7.1	Charge Point configured to report StopTransaction before going down.	No
AQ-7.2	Charge Point configured to report StopTransaction after going down and being back online again.	Yes



Other Relevant Settings

ID	Limit / Setting	Value
ORS-1	GetConfigurationMaxKeys	10
ORS-2	MeterValuesAlignedDataMaxLength	4096
ORS-3	MeterValuesSampledDataMaxLength	4096
ORS-4	Minimum MeterValueSampleInterval supported	10
ORS-5	Maximum MeterValueSampleInterval supported	1000
ORS-6	Minimum HeartbeatInterval supported	10
ORS-7	Maximum HeartbeatInterval supported	1000
ORS-9	StopTxnAlignedDataMaxLength	4096
ORS-10	StopTxnSampledDataMaxLength	4096
ORS-11	WebSocketPingInterval	2

ID	Firmware Management Settings	Value
ORS-16	Supported file transfer protocols	http, https



Performance Measurement Result

Name	Max Value	Unit	Description	
OCPP response timeout	5	seconds	The timeout used for exchanging OCPP response messages. Messages to the DUT can be handled within this timeout.	
OCPP triggered function timeout	20	seconds	The timeout used for when waiting for an OCPP function with its corresponding request message. Messages to the DUT can be handled within this timeout. This value excludes firmware, diagnostics and rebooting	
Transaction authorization time by RemoteStartTransaction	10	seconds	The time between the RemoteStartTransaction.req message and the corresponding StartTransaction.req. Only cases where the RemoteStartTransaction immediately results in an authorization followed by a StartTransaction.req are included.	
Transaction authorization end time by RemoteStopTransaction	10	seconds	The time between the RemoteStopTransaction.req message and the corresponding StopTransaction.req. Only cases where the RemoteStopTransaction immediately results in an end of the authorization followed by a StopTransaction.req are included.	

Name	Min Value	Max Value	Average Value	Unit
OCPP response timeout	0.39	1.38	0.68	seconds
OCPP triggered function timeout	0.95	1.47	1.22	seconds
Transaction authorization time by RemoteStartTransaction	6.07	6.07	6.07	seconds
Transaction authorization end time by RemoteStopTransaction	8.28	8.28	8.28	seconds

Communication technology used during	Mobile Network
performance measurement:	NODILE NELWOIK



Statement of Approval

Vendor			
Name	Cheong SangDon	Date: 2024-11-08	
Company	MOTREX EV	Signature:	
Department	R&D Center	Λ	
Position	СТО	Inn	
Location	Bucheon, Korea	100	

Test Laboratory				
Name	Philip YANG	Date: 2024-11-08		
Name reviewer	Joe Lee	Signature:		
Company	Korea Smart Grid Association			
Department	Quality Certification Center	2		
Position	Chief Researcher			
Location	Seoul, Korea			