

**Certificate Holder:** Kempower  
**Certificate Number:** OCA.0201.0105.CS  
**Product Type:** Charging Station  
**Product Designation:** Kempower Satellite with C501D6V3  
**Firmware Version:** 3.6.0  
**Certification Date:** June 19, 2025

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 2.0.1 (Edition 3 FINAL, 2024-05-06 including Errata 2025-04). The optional OCPP protocol features that are covered by this certificate can be found in the Abstract of the Test Report that is part of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in this complete test report.

Applied	Performed by / On	Document Evidence
Conformance testing according to the test specification referenced by the test report	Dekra Certification B.V June 19, 2025	OCPP-2.0.1-PICS-CS-2.0.3 Kempower

The abstract of test report is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

**ONOPH CARON**  
 Chairman



## Abstract of the Test Report

### Test Report OCPP 2.0.1 Certification

<b>Test laboratory:</b>	<b>Dekra Certification B.V</b>
Location:	Arnhem
Test Report Reference:	229884300
<b>Product Designation:</b>	<b>Kempower Satellite with C501D6V3</b>
Vendor name:	Kempower
Device Under Test:	Charging Station
Firmware Version:	3.6.0
Config ID:	B6E5329D-F5440B73

### Test Result Summary for the Certified Functionalities

Certification Profile	Test Result	Description
Core	Pass	Basic Charging Station functionality for booting, authorization, configuration, transactions, remote control, including basic security.
Advanced Security	Pass	Support for TLS with client authentication.
Local Authorization List Management	Not Tested	Support for local authorization list management and optionally of an authorization cache.
Smart Charging	Not Tested	Support for Smart Charging, to control charging.
Advanced Device Management	Not Tested	Support for the OCPP Device Model and advanced logging and monitoring.
Reservation	Not Tested	Support for reservation of a connector of a Charging Station.
Advanced User Interface	Not Tested	Support for tariff & cost and DisplayMessage functionality.
ISO 15118 Support	Not Tested	Support for ISO 15118 Smart Charging and Plug and Charge authorization.

## Hardware Feature Set

The Hardware Feature set is the actual set of relevant hardware properties of the product tested, that influence the OCPP messaging behavior. In the table below you can see for each hardware feature relevant for OCPP whether this is applicable for this product.

ID	Feature	Supported / Present
HFS-1	Has a detachable cable	No
HFS-2	Has a fixed cable	Yes
HFS-3	Has AC support	No
HFS-4	Has DC support	Yes
HFS-5	Has 1 phase support	No
HFS-6	Has 2 phase support	No
HFS-7	Has 3 phase support	No
HFS-8	No. EVSEs	2
HFS-9	Communication technology	Ethernet, LTE, WiFi
HFS-10	RFID readers	Single
HFS-11	DC power level	600
HFS-12	Number of displays	1

EVSE	Current	Phases	Connector	Type	Cable Type
1	DC		1	cCCS2	Fixed Cable
2	DC		1	cCCS2	Fixed Cable



## Optional Features

The OCPP specification contains many implementation options that can be selected by a vendor, often in the form of optional message fields or configuration variables, that can be used to support advanced functions. Whereas the certification profiles determine which OCPP functionality is implemented, the features describe how much of a certain functionality in a profile has been implemented. The tables below indicate per certification profiles, for each available optional feature within this profile, whether this has been implemented in this product and tested for conformance or not. Please refer to part 5 of the OCPP specification for the list of optional features and the reference to the relevant use cases in part 2 of the OCPP specification.

### Core

ID	Core Features	Supported / Present
C-01	Support for offline authorization of transactions	Yes
C-02	Support for allowing Offline Authorization for Unknown Ids	Yes
C-03	Support for maximizing energy for invalid ids	No
C-04	Support to limit StatusNotifications	No
C-06	Authorization status after cable disconnected on EV side	
C-06.1	Support for maintaining authorization when cable disconnected on EV side	No
C-06.2	Support for not maintaining authorization when cable disconnected on EV side	Yes
C-07	Support for using a Master Pass for charging stations with UI	No
C-08	Support for using a Master Pass for charging stations without UI	No
C-09	Supported Transaction Start points	
C-09.1	Start transaction options - EVConnected	Yes
C-09.2	Start transaction options - Authorized	Yes
C-09.3	Start transaction options - DataSigned	No
C-09.4	Start transaction options - PowerPathClosed	No
C-09.5	Start transaction options - EnergyTransfer	No
C-09.6	Start transaction options - ParkingBayOccupancy	No
C-10	Supported Transaction Stop points	
C-10.1	Stop transaction options - EVConnected	Yes
C-10.2	Stop transaction options - Authorized	Yes
C-10.3	Stop transaction options - PowerPathClosed	No
C-10.4	Stop transaction options - EnergyTransfer	No
C-10.5	Stop transaction options - ParkingBayOccupancy	No
C-12	Unlocking of connector when cable disconnected on EV side	

ID	Core Features	Supported / Present
C-12.1	Support for unlocking connector when cable disconnected on EV side	No
C-12.2	Support for not unlocking when cable disconnected on EV side	Yes
C-13	Support for Reset per EVSE	No
C-14	Support for retrieving / deleting CustomerInformation - CustomerIdentifier	No
C-20	Allowing New Sessions Pending a FirmwareUpdate	No
C-21	Support for queuing all or only Transaction related messages until they are delivered to the CSMS	Yes
C-23	Supported time sources	Heartbeat NTP
C-25	Support for setting a TimeOffset	No
C-26	Support for setting the TimeZone	No
C-28	Toggle sending clock aligned meter values when a transaction is ongoing / Idle	No
C-29	TriggerMessage	
C-29.1	Trigger message - MeterValues	Yes
C-29.2	Trigger message - TransactionEvent	Yes
C-29.3	Trigger message - LogStatusNotification	Yes
C-29.4	Trigger message - FirmwareStatusNotification	Yes
C-29.5	Trigger message - StatusNotification	Yes
C-29.6	Trigger message - BootNotification	Yes

ID	Authorization Options for Local Start	Tested During Certification
C-30	Authorization - using RFID ISO14443	Yes
C-31	Authorization - using RFID ISO15693	No
C-32	Authorization - using KeyCode	No
C-33	Authorization - using locally generated id	No
C-34	Authorization - MacAddress	No
C-35	Authorization - NoAuthorization	No

ID	Authorization Options for Remote Start	Tested During Certification
C-36	Authorization - using RFID ISO14443	Yes
C-37	Authorization - using RFID ISO15693	No
C-38	Authorization - using centrally, in the CSMS generated id	No
C-39	Authorization - NoAuthorization	No

ID	Metervalues	Tested During Certification	Supported According to Vendor
C-40	Supported MeterValue Measurands		
C-40.1	SampledTxEStarted Measurands	Power.Active.Import Energy.Active.Import.Register Current.Import Voltage Power.Offered SoC Current.Offered	Energy.Active.Import.Register Current.Import Current.Offered Power.Active.Import Power.Offered Voltage SoC
C-40.2	SampledTxEUpdated Measurands	Power.Active.Import Energy.Active.Import.Register Current.Import Voltage Power.Offered SoC Current.Offered	Energy.Active.Import.Register Current.Import Current.Offered Power.Active.Import Power.Offered Voltage SoC
C-40.3	SampledTxEEnded Measurands	Power.Active.Import Energy.Active.Import.Register Current.Import Voltage Power.Offered SoC Current.Offered	Energy.Active.Import.Register Current.Import Current.Offered Power.Active.Import Power.Offered Voltage SoC
C-40.4	AlignedData Measurands	Power.Active.Import Energy.Active.Import.Register Current.Import Voltage Power.Offered SoC Current.Offered	Energy.Active.Import.Register Current.Import Current.Offered Power.Active.Import Power.Offered Voltage SoC

ID	Metervalues	Tested During Certification	Supported According to Vendor
C-40.5	AlignedDataTxEnded Measurands	Power.Active.Import Energy.Active.Import.Register Current.Import Voltage Power.Offered SoC Current.Offered	Energy.Active.Import.Register Current.Import Current.Offered Power.Active.Import Power.Offered Voltage SoC

ID	Cipher Suites	Supported / Present
C-41	Supported Cipher Suites	TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_EC DHE_ECDSA_WITH_AES_256_GCM_SHA384

ID	Core Features	Supported / Present
C-42	Signed Metervalues	No
C-43	Install Firmware with ongoing transaction	No
C-47	Support for falling back to default OCPP reconnection mechanism when NetworkConnection profile connection has failed	Yes
C-48	Authorization of remote start	
C-48.1	Option for authorization in case of a remote start	Yes
C-48.2	Option for no authorization in case of a remote start	Yes
C-58	Option for disabling remote authorization	No
C-49	Authorization Cache	Yes
C-59	Option for disabling remote authorization for cached invalid idTokens	No
C-51	Configurable TxStartPoint	Yes
C-52	Configurable TxStopPoint	Yes
C-53	Support for lifetime cached token	Yes
C-54	Supported policies for replacing cached entries	No
C-56	Support for providing the SummaryInventory	No
C-57	Support for cancelling ongoing log file upload	No
C-60	Support for cancelling ongoing firmware update	No

## Advanced Security

ID	Certification Profile: Advanced Security	Supported / Present
AS-2	Additional root certificate check mechanism implemented	No
AS-3	Update Charging Station Certificate - CertificateSignedRequest Timeout	No

### Additional Questions

The table below lists a number of questions that are needed for determining the complete list of conformance test for this product.

ID	Additional Questions for Lab Testing	Answer
AQ-1	Can the last CSMSRootCertificate can be removed?	No
AQ-2	Does the Charging Station have a cable lock, which prevents the EV driver to connect the EV and EVSE before authorization?	No
AQ-3	Can the last ChargingStationCertificate be removed?	Yes
AQ-4	Is there at least one unsupported NumberOfPhases?	No
AQ-5	Does the Charging Station have at least one hardWired monitor?	No
AQ-6	Does the Charging Station have a pre-configured monitor?	No
AQ-7	Is your Charging Station able to download firmware while there is an ongoing transaction?	Yes
AQ-8	Does your Charging Station enforce a selection of EVSE prior to authorization?	Yes
AQ-9	Does your Charging Station support charging an EV using IEC 61851-1?	No
AQ-10	Does your Charging Station support setting a Delta monitor on the WriteOnly component.variable SecurityCtrlr.BasicAuthPassword?	No
AQ-11	Does your Charging Station support a combined charging station Certificate	No

## Other Relevant Settings

The table below lists a number of settings that are needed for configuring the test setup for the conformance test for this product.

ID	Limit / Setting	Value
ORS-1	ItemsPerMessageGetReport	512
ORS-2	ItemsPerMessageGetVariables	512
ORS-3	ItemsPerMessageSetVariables	512
ORS-4	BytesPerMessageGetReport	20000
ORS-5	BytesPerMessageGetVariables	20000
ORS-6	BytesPerMessageSetVariables	20000
ORS-16	WebSocketPingInterval	5

ID	Security Related Settings	Value
ORS-17	CertificateEntries	500

ID	Firmware Management Settings	Value
ORS-24	Supported file transfer protocols	FTP

## Additional Network Communication Ports

Description	Protocol	Network Port	Direction	Secured
Maintenance Tool	https	8443	Inbound	Yes

## Vendor Specific Settings

The table below should contain all relevant non-OCPP settings of the System Under Test that are relevant for the test laboratory and for the correct OCPP-compliant functioning :

Configuration Setting	Configured Value	Description
AuthCtrlr.Enabled	True	Authorization must be enabled

Configuration Setting	Configured Value	Description
OCPPCommCtrlr.SendBootNotificationOnReconnect	False	must be disabled
OCPPCommCtrlr.WebSocketPingInterval	5	Some tests need small interval
Controlling system	Device	Must not be cloud
SECC type	v2	Must not be v3. This is defined in chargers system structure.
SecurityCtrlr.OrganizationName	Kempower	Must be defined
ISO15118Ctrlr.PncOperator	external	Must be defined
AuthCtrlr.AuthorizationTimeOut	0	Must be 0 seconds
noTLSv13	True	TLS v1.3 must be disabled from CE connectivity advanced settings
SmartChargingCtrlr.Enabled	False	Smart charging must be disabled

## Performance Measurement Result

The tables below shows the list of key performance indicators that are measured during the conformance test. The first table indicates the values that the vendor indicates that are valid maximum values for this product. The second table lists the actual performance measurements during the tests performed in a controlled environment.


Name	Max Value	Unit	Description
OCPP response time	30	seconds	The response time for when waiting for an OCPP response message after sending an OCPP request message. This entails all OCPP messages. Messages to the DUT can be handled within this timeout.
OCPP triggered function response time	30	seconds	The response time used when waiting for an asynchronous OCPP report after requesting this report.
Transaction authorization time by RequestStartTransactionRequest	30	seconds	The time between a RequestStartTransactionRequest and the corresponding TransactionEventRequest. Only cases where the RequestStartTransactionRequest immediately results in an authorization followed by a TransactionEventRequest, without the need of any additional manual actions or chargingState transitions inbetween are included.
Transaction authorization time by RequestStopTransactionRequest	30	seconds	The time between a RequestStopTransactionRequest and the corresponding TransactionEventRequest. Only cases where the RequestStopTransactionRequest immediately results in an end of the authorization followed by a TransactionEventRequest, that do not contain transactionInfo.chargingState = EVConnected are included.

Name	Min Value	Max Value	Average Value	Unit
OCPP response time	0.04	12.98	0.12	seconds
OCPP triggered function response time	0.06	0.63	0.24	seconds
Transaction authorization time by RequestStartTransactionRequest	0.23	0.53	0.40	seconds
Transaction authorization end time by RequestStopTransactionRequest	not measurable	not measurable	not measurable	seconds

Communication technology used during performance measurement	Ethernet
--	----------

## Statement of Approval

Vendor		
Name	Antti Kärkkäinen	Date: 2025-06-19
Company	Kempower	Signature:
Department	Product Development	
Position	Vice President, Product Development	
Location	Lahti, Finland	

Test Laboratory		
Name	Yigit Karabulut	Date: 2025-06-19
Name reviewer	Mohammed Abdi	Signature:
Company	Dekra Certification B.V	
Department	CE	
Position	Test Engineer	
Location	Arnhem	

OCTT Version	Release_2025-04
OCTT Instance ID	237ae1d5c2f67827ac6a3ebdeba7dd55
Firmware image hash	42ffe39edf815ff38f0e8f91e7d467ed5a5cda0190ce24fdb753316cb67e93f0