



Certificate Holder: Loop Global
Certificate Number: OCA.0016.1130.CS
Product Type: Charging Station
Product Designation: EVS-40A-L2-001
Firmware Version: v01.00 OCPP 1.6J
Certification Date: November 18, 2025

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 (Edition 2 FINAL, 2017-09-28 including Errata 2025-04) and Security Whitepaper Edition 3 (Improved security for OCPP 1.6-J v1.3, 2022-02-17). The optional OCPP protocol features that are covered by this certificate can be found in the Abstract of the Test Report that is part of this certificate.

Applied	Performed by / On	Document Evidence
Conformance testing according to the test specification referenced by the test report	DEKRA Certification, Inc September 23, 2025	LOOP_40A_OCPP-1.6-PICS-CS-2.1.0_signed_updated

The abstract of test report is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON
Chairman

Authenticity of this certificate can be verified at www.openchargealliance.org



Abstract of the Test Report

Test Report OCPP1.6 Certification

Test laboratory:	DEKRA Certification, Inc
Location:	Sterling, VA
Test Report Reference:	04501RCO.002
Product Designation:	EVS-40A-L2-001
Vendor name:	Loop Global
Device Under Test:	Charging Station
Firmware Version:	v01.00 OCPP 1.6J
Config ID:	D6A688AE-B7652F79

Test Result Summary for the Certified Functionalities

Certification Profile	Test Result	Description
Core	Pass	Basic Charging Station, functionality for booting, authorization, configuration, transactions, remote control.
Firmware Management	Pass	Support for firmware update management and diagnostic log file download.
Local Authorization List Management	Pass	Features to manage a local list in the charging station containing authorization data for whitelisting users.
Smart Charging	Pass	Support for Smart Charging, to control charging.
Remote Trigger	Pass	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.
Reservation	Pass	Support for reservation of a connector of a Charging Station.

Certification Extension	Test Result	Description
Security extension	Pass	Implementation of the whitepaper: Improved security for OCPP 1.6-J

Authenticity of this certificate can be verified at www.openchargealliance.org



OCPP 1.6
Security
Certified



OCPP 1.6
Fully
Certified

Hardware Feature Set

The Hardware Feature set is the actual set of relevant hardware properties of the product tested, that influence the OCPP messaging behavior. In the table below you can see for each hardware feature relevant for OCPP whether this is applicable for this product.

ID	Feature	Supported / Present
HFS-1	Has a detachable cable	No
HFS-2	Has a fixed cable	Yes
HFS-3	Has AC support	Yes
HFS-4	Has DC support	No
HFS-5	Has 1 phase support	Yes
HFS-6	Has 2 phase support	No
HFS-7	Has 3 phase support	No
HFS-8	No. Connectors	1
HFS-9	Communication technology	Wi-Fi, LTE, Ethernet
HFS-10	RFID readers	Single

Connector	Current	Phases	Type	Cable Type
1	AC	1	cType1	Fixed Cable



Authenticity of this certificate can be verified at www.openchargealliance.org



Optional Features

The OCPP specification contains many implementation options that can be selected by a vendor, often in the form of optional message fields or configuration variables, that can be used to support advanced functions. Whereas the certification profiles determine which OCPP functionality is implemented, the features describe how much of a certain functionality in a profile has been implemented. The tables below indicate per certification profiles, for each available optional feature within this profile, whether this has been implemented in this product and tested for conformance or not.

Core		
ID	Core Features	Supported / Present
C-01	Support for offline authorization of transactions	Yes
C-02	Support for allowing Offline Authorization for Unknown Ids	Yes
C-03	Support for maximizing energy for invalid ids	Yes
C-04	Authorization Cache	Yes
C-05	Support to limit StatusNotifications	Yes
C-06	Authorization status after cable disconnected on EV side	
C-06.1	Support for maintaining authorization when cable disconnected on EV side	Yes
C-06.2	Support for not maintaining authorization when cable disconnected on EV side	Yes
C-07	Support for local start	Yes
C-08	Support for local stop	Yes
C-10	Unlocking of connector when cable disconnected on EV side	
C-10.1	Support for unlocking connector when cable disconnected on EV side	No
C-10.2	Support for not unlocking when cable disconnected on EV side	Yes

ID	Metervalue	Tested During Certification	Supported According to Vendor
C-09	Supported MeterValue Measurands		



ID	Metervalues	Tested During Certification	Supported According to Vendor
C-09.1	MeterValuesSampled Data	Voltage Temperature Power.Active.Import Current.Offered Energy.Active.Import.Register Current.Import Power.Offered	Current.Import Current.Offered Energy.Active.Import.Register Power.Active.Import Power.Offered Temperature Voltage
C-09.2	MeterValuesAligned Data	Energy.Active.Import.Interval Voltage Temperature Power.Active.Import Current.Offered Energy.Active.Import.Register Current.Import Power.Offered	Current.Import Current.Offered Energy.Active.Import.Register Energy.Active.Import.Interval Power.Active.Import Power.Offered Temperature Voltage

Smart Charging

ID	Certification Profile: Smart Charging	Supported / Present
SC-1	Supported charging rate units	
SC-1.1	A	Yes
SC-1.2	W	Yes

Reservation

ID	Certification Profile: Reservation	Supported / Present
R-1	Support reservations of entire Charging Station	Yes

Firmware Management



ID	Certification Profile: Firmware Management	Supported / Present
F-1	Support for Secure Firmware Updates	Yes

Security

ID	Security Extension	Supported / Present
SEC-1	Security Profile 1: Unsecured Transport with Basic Authentication	Yes
SEC-2	Security Profile 2: TLS with Basic Authentication	Yes
SEC-3	Security Profile 3: TLS with Client Side Certificates	No

Security Cipher Suites

ID	Security Extension : Cipher Suites	Supported / Present
SEC-4	Supported Cipher Suites	TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_RSA_WITH_AES_128_GCM_SHA256,TLS_RSA_WITH_AES_256_GCM_SHA384

Additional Questions

The table below lists a number of questions that are needed for determining the complete list of conformance test for this product.

ID	Additional Questions for Lab Testing	Answer
AQ-1	Can the last CentralSystemRootCertificate be removed?	Yes
AQ-2	Does the Charging Station have a cable lock, which prevents the EV driver to connect the EV and EVSE before authorization?	No
AQ-3	Can the last ChargePointCertificate be removed?	Yes
AQ-4	Is your Charging Station able to download firmware while there is an ongoing transaction?	Yes
AQ-5	Does your Charging Station enforce a selection of EVSE prior to authorization?	No



ID	Additional Questions for Lab Testing	Answer
AQ-6	Does your Charging Station support charging an EV using IEC 61851-1?	Yes
AQ-7	Reporting of StopTransaction after power loss	
AQ-7.1	Charge Point configured to report StopTransaction before going down.	No
AQ-7.2	Charge Point configured to report StopTransaction after going down and being back online again.	Yes

Other Relevant Settings

The table below lists a number of settings that are needed for configuring the test setup for the conformance test for this product.

ID	Limit / Setting	Value
ORS-1	GetConfigurationMaxKeys	160
ORS-2	MeterValuesAlignedDataMaxLength	8
ORS-3	MeterValuesSampledDataMaxLength	7
ORS-4	Minimum MeterValueSampleInterval supported	0
ORS-5	Maximum MeterValueSampleInterval supported	86400
ORS-6	Minimum HeartbeatInterval supported	0
ORS-7	Maximum HeartbeatInterval supported	86400
ORS-9	StopTxnAlignedDataMaxLength	7
ORS-10	StopTxnSampledDataMaxLength	6
ORS-11	WebSocketPingInterval	120

ID	Certification Profile: Local Authorization List Management	Value
ORS-12	LocalAuthListMaxLength	1000
ORS-13	SendLocalListMaxLength	1000

ID	Certification Profile: Smart Charging	Value
ORS-14	ChargingProfileMaxStackLevel	99
ORS-15	ChargingScheduleMaxPeriods	32
ORS-19	MaxChargingProfilesInstalled	10



ID	Firmware Management Settings	Value
ORS-16	Supported file transfer protocols	HTTP FTP

ID	Security Extension	Value
ORS-17	CertificateSignedMaxChainSize	10
ORS-18	CertificateStoreMaxLength	10



Performance Measurement Result

The tables below shows the list of key performance indicators that are measured during the conformance test. The first table indicates the values that the vendor indicates that are valid maximum values for this product. The second table lists the actual performance measurements during the tests performed in a controlled environment.

Name	Max Value	Unit	Description
OCPP response timeout	20	seconds	The timeout used for exchanging OCPP response messages. Messages to the DUT can be handled within this timeout.
OCPP triggered function timeout	20	seconds	The timeout used for when waiting for an OCPP function with its corresponding request message. Messages to the DUT can be handled within this timeout. This value excludes firmware, diagnostics and rebooting
Transaction authorization time by RemoteStartTransaction	20	seconds	The time between the RemoteStartTransaction.req message and the corresponding StartTransaction.req. Only cases where the RemoteStartTransaction immediately results in an authorization followed by a StartTransaction.req are included.
Transaction authorization end time by RemoteStopTransaction	20	seconds	The time between the RemoteStopTransaction.req message and the corresponding StopTransaction.req. Only cases where the RemoteStopTransaction immediately results in an end of the authorization followed by a StopTransaction.req are included.

Name	Min Value	Max Value	Average Value	Unit
OCPP response timeout	1.31	5.04	2.80	seconds
OCPP triggered function timeout	2.33	4.35	3.33	seconds
Transaction authorization time by RemoteStartTransaction	3.57	3.57	3.57	seconds
Transaction authorization end time by RemoteStopTransaction	5.52	7.21	6.37	seconds

Communication technology used during performance measurement	WiFi
--	------



Statement of Approval

Vendor

Name	Son Dang	Date: 2025-11-17
Company	Loop Global	Signature:
Department	Product	
Position	Chief Product Officer	
Location	1700 E Walnut Ave. El Segundo CA 90245	

Test Laboratory

Name	Avinash Koduri	Date: 2025-11-18
Name reviewer	Gonzalo Casado	Signature:
Company	DEKRA Certification, Inc	
Department	Connectivity & E-Mobility Services	
Position	Lab Manager	
Location	Sterling, VA	

OCTT Version	Release_2025-06
OCTT Instance ID	c601c262592301a8bddd6be2098b2f86
Firmware image hash	bdf673b5864a35b3fc64aab4cb6767b89c8e21246cf7ba000cf6f53b825fb856

Authenticity of this certificate can be verified at www.openchargealliance.org