

OCPP WHITE LABEL CERTIFICATE

This certificate is issued on an attest basis and relies solely on information provided by the parties named below; the Open Charge Alliance has not performed any re-testing of the rebranded product

White Label Certificate

Holder: American Powerpump

White Label Certificate Number: W01.OCA.0201.0123.CS

Product type: Charging Station

Product designation: AC5500-G40

Firmware version: V03.13.00

Date of registration: March 3rd, 2026

This white label certificate attests that the above mentioned product is a rebranded version of a product that successfully completed certification testing as stated in the attached OCA certificate. No re-testing of the rebranded product has been performed by the Open Charge Alliance. The reference specification and optional OCPP protocol features that are covered by the original certificate can be found in abstract of the Test Report that is part of the attached certificate.

White Label Certificate Holder and Certificate Holder from the original certified product attest that both the hardware and software (version) on these products are the same.

Based on information and documents provided by the White Label Certificate Holder and Certificate Holder from the original certified product, the Open Charge Alliance performed a verification limited to the items necessary for the stated purpose. Reasonable steps to validate the submitted information against available sources have been taken; however, no audit or exhaustive review was conducted, and the Open Charge Alliance relies on the accuracy and completeness of the materials supplied by mentioned parties. Accordingly, the Open Charge Alliance makes no representation or warranty, express or implied, as to the truth, completeness, or future accuracy of the information and accepts no responsibility or liability if any part of it is later found to be inaccurate, incomplete, or misleading. This white label certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only. Dutch law applies to this certificate.



For the Open Charge Alliance:

ONOPH CARON
Chairman



For American
Powerpump:

**Pascale van
Cleemput**
Manager



For Xiamen
Topstar Co., Ltd.:

Guolin Chen
Manager



Certificate Holder: Xiamen Topstar Co., Ltd.
Certificate Number: OCA.0201.0123.CS
Product Type: Charging Station
Product Designation: TSEA240V/40AUS-ZRGMP-C
Firmware Version: V03.13.00
Certification Date: November 13, 2025

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 2.0.1 (Edition 3 FINAL, 2024-05-06 including Errata 2025-09). The optional OCPP protocol features that are covered by this certificate can be found in the Abstract of the Test Report that is part of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in this complete test report.

Applied	Performed by / On	Document Evidence
Conformance testing according to the test specification referenced by the test report	DNV Singapore Pte Ltd November 11, 2025	PICS_PRJ_10574735

The abstract of test report is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON
 Chairman



Abstract of the Test Report

Test Report OCPP 2.0.1 Certification

Test laboratory:	DNV Singapore Pte Ltd
Location:	DNV Singapore, Singapore
Test Report Reference:	PICS_PRJ_10574735
Test Location	Singapore
Product Designation:	TSEA240V/40AUS-ZRGMP-C
Vendor name:	Xiamen Topstar Co., Ltd.
Device Under Test:	Charging Station
Firmware Version:	V03.13.00
Config ID:	3E94C08E-6E94D07A

Test Result Summary for the Certified Functionalities

Certification Profile	Test Result	Description
Core	Pass	Basic Charging Station functionality for booting, authorization, configuration, transactions, remote control, including basic security.
Advanced Security	Pass	Support for TLS with client authentication.
Local Authorization List Management	Pass	Support for local authorization list management and optionally of an authorization cache.
Smart Charging	Not Tested	Support for Smart Charging, to control charging.
Advanced Device Management	Not Tested	Support for the OCPP Device Model and advanced logging and monitoring.
Reservation	Pass	Support for reservation of a connector of a Charging Station.
Advanced User Interface	Not Tested	Support for tariff & cost and DisplayMessage functionality.
ISO 15118 Support	Not Tested	Support for ISO 15118 Smart Charging and Plug and Charge authorization.

Hardware Feature Set

The Hardware Feature set is the actual set of relevant hardware properties of the product tested, that influence the OCPP messaging behavior. In the table below you can see for each hardware feature relevant for OCPP whether this is applicable for this product.

ID	Feature	Supported / Present
HFS-1	Has a detachable cable	No
HFS-2	Has a fixed cable	Yes
HFS-3	Has AC support	Yes
HFS-4	Has DC support	No
HFS-5	Has 1 phase support	Yes
HFS-6	Has 2 phase support	No
HFS-7	Has 3 phase support	No
HFS-8	No. EVSEs	1
HFS-9	Communication technology	WiFi, Ethernet, Mobile Network
HFS-10	RFID readers	Single
HFS-12	Number of displays	1

EVSE	Current	Phases	Connector	Type	Cable Type
1	AC	1	1	cType1	Fixed Cable



Optional Features

The OCPP specification contains many implementation options that can be selected by a vendor, often in the form of optional message fields or configuration variables, that can be used to support advanced functions. Whereas the certification profiles determine which OCPP functionality is implemented, the features describe how much of a certain functionality in a profile has been implemented. The tables below indicate per certification profiles, for each available optional feature within this profile, whether this has been implemented in this product and tested for conformance or not. Please refer to part 5 of the OCPP specification for the list of optional features and the reference to the relevant use cases in part 2 of the OCPP specification.

Core

ID	Core Features	Supported / Present
C-01	Support for offline authorization of transactions	Yes
C-02	Support for allowing Offline Authorization for Unknown Ids	Yes
C-03	Support for maximizing energy for invalid ids	No
C-04	Support to limit StatusNotifications	No
C-06	Authorization status after cable disconnected on EV side	
C-06.1	Support for maintaining authorization when cable disconnected on EV side	Yes
C-06.2	Support for not maintaining authorization when cable disconnected on EV side	Yes
C-07	Support for using a Master Pass for charging stations with UI	Yes
C-08	Support for using a Master Pass for charging stations without UI	Yes
C-09	Supported Transaction Start points	
C-09.1	Start transaction options - EVConnected	No
C-09.2	Start transaction options - Authorized	Yes
C-09.3	Start transaction options - DataSigned	No
C-09.4	Start transaction options - PowerPathClosed	No
C-09.5	Start transaction options - EnergyTransfer	No
C-09.6	Start transaction options - ParkingBayOccupancy	No
C-10	Supported Transaction Stop points	
C-10.1	Stop transaction options - EVConnected	No
C-10.2	Stop transaction options - Authorized	No
C-10.3	Stop transaction options - PowerPathClosed	Yes
C-10.4	Stop transaction options - EnergyTransfer	No
C-10.5	Stop transaction options - ParkingBayOccupancy	No

ID	Core Features	Supported / Present
C-12	Unlocking of connector when cable disconnected on EV side	
C-12.1	Support for unlocking connector when cable disconnected on EV side	No
C-12.2	Support for not unlocking when cable disconnected on EV side	Yes
C-13	Support for Reset per EVSE	No
C-14	Support for retrieving / deleting CustomerInformation - CustomerIdentifier	No
C-20	Allowing New Sessions Pending a FirmwareUpdate	No
C-21	Support for queuing all or only Transaction related messages until they are delivered to the CSMS	No
C-23	Supported time sources	Heartbeat
C-25	Support for setting a TimeOffset	Yes
C-26	Support for setting the TimeZone	No
C-28	Toggle sending clock aligned meter values when a transaction is ongoing / Idle	Yes
C-29	TriggerMessage	
C-29.1	Trigger message - MeterValues	Yes
C-29.2	Trigger message - TransactionEvent	Yes
C-29.3	Trigger message - LogStatusNotification	Yes
C-29.4	Trigger message - FirmwareStatusNotification	Yes
C-29.5	Trigger message - StatusNotification	Yes
C-29.6	Trigger message - BootNotification	Yes

ID	Authorization Options for Local Start	Tested During Certification
C-30	Authorization - using RFID ISO14443	Yes
C-31	Authorization - using RFID ISO15693	No
C-32	Authorization - using KeyCode	No
C-33	Authorization - using locally generated id	No
C-34	Authorization - MacAddress	No
C-35	Authorization - NoAuthorization	No

ID	Authorization Options for Local Stop	Tested During Certification
C-70	Authorization - using RFID ISO14443	Yes
C-71	Authorization - using RFID ISO15693	No

ID	Authorization Options for Local Stop	Tested During Certification
C-72	Authorization - using KeyCode	No
C-75	Authorization - NoAuthorization	No

ID	Authorization Options for Remote Start	Tested During Certification
C-36	Authorization - using RFID ISO14443	Yes
C-37	Authorization - using RFID ISO15693	No
C-38	Authorization - using centrally, in the CSMS generated id	Yes
C-39	Authorization - NoAuthorization	No

ID	Metervalues	Tested During Certification	Supported According to Vendor
C-40	Supported MeterValue Measurands		
C-40.1	SampledTxBegan Measurands	Energy.Active.Import.Register	Energy.Active.Import.Register
C-40.2	SampledTxBegan Measurands	Power.Active.Import Voltage Energy.Active.Import.Register Current.Import	Energy.Active.Import.Register Current.Import Power.Active.Import Voltage Current.Offered Power.Offered
C-40.3	SampledTxEnded Measurands	Energy.Active.Import.Register	Energy.Active.Import.Register
C-40.4	AlignedData Measurands	Energy.Active.Import.Register	Energy.Active.Import.Register Current.Import Power.Active.Import Voltage Current.Offered Power.Offered
C-40.5	AlignedDataTxEnded Measurands	Energy.Active.Import.Register	Energy.Active.Import.Register

ID	Cipher Suites	Supported / Present
C-41	Supported Cipher Suites	TLS_RSA_WITH_AES_128_GCM_SHA256 TLS_RSA_WITH_AES_256_GCM_SHA384

ID	Core Features	Supported / Present
C-42	Signed Metervalues	No
C-43	Install Firmware with ongoing transaction	No
C-47	Support for falling back to default OCPP reconnection mechanism when NetworkConnection profile connection has failed	No
C-48	Authorization of remote start	
C-48.1	Option for authorization in case of a remote start	Yes
C-48.2	Option for no authorization in case of a remote start	Yes
C-58	Option for disabling remote authorization	Yes
C-49	Authorization Cache	Yes
C-59	Option for disabling remote authorization for cached invalid idTokens	Yes
C-51	Configurable TxStartPoint	No
C-52	Configurable TxStopPoint	No
C-53	Support for lifetime cached token	Yes
C-54	Supported policies for replacing cached entries	No
C-56	Support for providing the SummaryInventory	No
C-57	Support for cancelling ongoing log file upload	No
C-60	Support for cancelling ongoing firmware update	No
C-61	Security Profile 1 - Unsecured Transport with Basic Authentication	Yes

Advanced Security

ID	Certification Profile: Advanced Security	Supported / Present
AS-2	Additional root certificate check mechanism implemented	No
AS-3	Update Charging Station Certificate - CertificateSignedRequest Timeout	Yes

Reservation

ID	Certification Profile: Reservation	Supported / Present
R-1	Support for reservations of connectorType	Yes
R-2	Support for reservation of unspecified EVSE	Yes
R-3	Support for disabling Reservations	Yes

Local Authorization List Management

ID	Certification Profile: Local Authorization List Management	Supported / Present
LA-1	Authorization list support	Yes
LA-3	Option for disabling remote authorization for invalid idTokens stored at the Local Authorization List	Yes

Additional Questions

The table below lists a number of questions that are needed for determining the complete list of conformance test for this product.

ID	Additional Questions for Lab Testing	Answer
AQ-1	Can the last CSMSRootCertificate be removed?	Yes
AQ-2	Does the Charging Station have a cable lock, which prevents the EV driver to connect the EV and EVSE before authorization?	No
AQ-3	Can the last ChargingStationCertificate be removed?	Yes
AQ-4	Is there at least one unsupported NumberOfPhases?	No
AQ-5	Does the Charging Station have at least one hardWired monitor?	No
AQ-6	Does the Charging Station have a pre-configured monitor?	No
AQ-7	Is your Charging Station able to download firmware while there is an ongoing transaction?	Yes
AQ-8	Does your Charging Station enforce a selection of EVSE prior to authorization?	Yes

ID	Additional Questions for Lab Testing	Answer
AQ-9	Does your Charging Station support charging an EV using IEC 61851-1?	Yes
AQ-10	Does your Charging Station support setting a Delta monitor on the WriteOnly component.variable SecurityCtrlr.BasicAuthPassword?	No
AQ-11	Does your Charging Station support a combined charging station Certificate	No
AQ-18	Does your Charging Station have at least one connector with an mechanized locking mechanism on Charging Station side?	No

Other Relevant Settings

The table below lists a number of settings that are needed for configuring the test setup for the conformance test for this product.

ID	Limit / Setting	Value
ORS-1	ItemsPerMessageGetReport	5
ORS-2	ItemsPerMessageGetVariables	5
ORS-3	ItemsPerMessageSetVariables	5
ORS-4	BytesPerMessageGetReport	1024
ORS-5	BytesPerMessageGetVariables	1024
ORS-6	BytesPerMessageSetVariables	1024
ORS-7	Minimum MessageAttemptIntervalTransactionEvent supported	5
ORS-9	Minimum SampledDataTxUpdatedInterval supported	10
ORS-11	Minimum HeartbeatInterval supported	10
ORS-12	Maximum HeartbeatInterval supported	3600
ORS-14	Minimum WebSocketPingInterval supported	0
ORS-15	Maximum WebSocketPingInterval supported	3600
ORS-16	WebSocketPingInterval	30

ID	Security Related Settings	Value
ORS-17	Maximum CertificateEntries supported	5
ORS-18	MaxCertificateChainSize	5600

ID	Certification Profile: Local Authorization List Management	Value
ORS-19	LocalAuthListEntries	1024
ORS-20	ItemsPerMessageSendLocalList	16
ORS-21	BytesPerMessageSendLocalList	1024

ID	Firmware Management Settings	Value
ORS-24	Supported file transfer protocols	HTTP FTP

Performance Measurement Result

The tables below shows the list of key performance indicators that are measured during the conformance test. The first table indicates the values that the vendor indicates that are valid maximum values for this product. The second table lists the actual performance measurements during the tests performed in a controlled environment.

Name	Max Value	Unit	Description
OCPP response time	30	seconds	The response time for when waiting for an OCPP response message after sending an OCPP request message. This entails all OCPP messages. Messages to the DUT can be handled within this timeout.
OCPP triggered function response time	30	seconds	The response time used when waiting for an asynchronous OCPP report after requesting this report.
Transaction authorization time by RequestStartTransactionRequest	10	seconds	The time between a RequestStartTransactionRequest and the corresponding TransactionEventRequest. Only cases where the RequestStartTransactionRequest immediately results in an authorization followed by a TransactionEventRequest, without the need of any additional manual actions or chargingState transitions inbetween are included.
Transaction authorization end time by RequestStopTransactionRequest	10	seconds	The time between a RequestStopTransactionRequest and the corresponding TransactionEventRequest. Only cases where the RequestStopTransactionRequest immediately results in an end of the authorization followed by a TransactionEventRequest, that do not contain transactionInfo.chargingState = EVConnected are included.

Name	Min Value	Max Value	Average Value	Unit
OCPP response time	0.29	29.06	0.63	seconds
OCPP triggered function response time	0.61	26.65	7.58	seconds
Transaction authorization time by RequestStartTransactionRequest	1.75	5.72	3.18	seconds
Transaction authorization end time by RequestStopTransactionRequest	not measurable	not measurable	not measurable	seconds

Communication technology used during performance measurement	WiFi
--	------

Statement of Approval

Vendor		
Name	Chi Wei	Date: 2025-11-13
Company	Xiamen Topstar Co., Ltd.	Signature:
Department	Technical Management	
Position	Manager	
Location	Xiamen, China	

Test Laboratory		
Name	Huang Qilin	Date: 2025-11-13
Company	DNV Singapore Pte Ltd	Signature:
Department	Energy Systems	
Position	Singapore	
Location	DNV Singapore, Singapore	

OCTT Version	Release_2025-09_v3
OCTT Instance ID	341870e80ca16f1a69fd7246f502e765
Firmware image hash	02942e64615e3bbc06bc56089a3e25da79f7d5792e5d4a98a9204809c75eba7d