



Certificate Holder: EGTRONICS CO., LTD.
Certificate Number: F01.OCA.0016.1218.CS
Product Type: Charging Station
Product Designation: EGMI205001
Firmware Version: 1.1.1
Certification Date: April 7, 2026

This certificate attests that the above mentioned product - a representative product for an OCPP product family - successfully completed certification testing in conformance with the reference specification OCPP 1.6 (Edition 2 FINAL, 2017-09-28 including Errata 2025-04) and Security Whitepaper Edition 4 (Improved security for OCPP 1.6-J v1.4, 2026-02-05). The optional OCPP protocol features that are covered by this certificate can be found in the Abstract of the Test Report that is part of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in this complete test report.

Applied	Performed by / On	Document Evidence
Conformance testing according to the test specification referenced by the test report	Korea Testing Certification institute April 6, 2026	KTC2026-00344_OCPP-1.6-PICS-CS-3.0.5_EGMI205001_260407

The abstract of test report is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON
Chairman

Abstract of the Test Report

Test Report OCPP 1.6 Certification

Test laboratory:	Korea Testing Certification institute
Location:	Gyeonggi-do, Korea
Test Report Reference:	KTC2026-00344
Test Location	KTC Lab, Gyeonggi-do, Korea
Product Designation:	EGMI205001
Vendor name:	EGTRONICS CO., LTD.
Device Under Test:	Charging Station
Firmware Version:	1.1.1.1
Config ID:	60B00282-DE45E080

Test Result Summary for the Certified Functionalities

Certification Profile	Test Result	Description
Core	Pass	Basic Charging Station, functionality for booting, authorization, configuration, transactions, remote control, secure firmware updates and Security Profile 2.
Advanced Security	Pass	Support for TLS with client authentication.
Smart Charging	Not Tested	Support for Smart Charging, to control charging.

Hardware Feature Set

The Hardware Feature set is the actual set of relevant hardware properties of the product tested, that influence the OCPP messaging behavior. In the table below you can see for each hardware feature relevant for OCPP whether this is applicable for this product.

ID	Feature	Supported / Present
HFS-1	Has a detachable cable	No
HFS-2	Has a fixed cable	Yes
HFS-3	Has AC support	No
HFS-4	Has DC support	Yes
HFS-5	Has 1 phase support	No
HFS-6	Has 2 phase support	No
HFS-7	Has 3 phase support	No
HFS-8	No. Connectors	2
HFS-9	Communication technology	Ethernet
HFS-10	RFID readers	Single - not tested for OCPP Certification
HFS-11	DC power level	50

Connector	Current	Phases	Type	Cable Type
1	DC		cCCSI	Fixed Cable
2	DC		cCCSI	Fixed Cable



Optional Features

The OCPP specification contains many implementation options that can be selected by a vendor, often in the form of optional message fields or configuration variables, that can be used to support advanced functions. Whereas the certification profiles determine which OCPP functionality is implemented, the features describe how much of a certain functionality in a profile has been implemented. The tables below indicate per certification profiles, for each available optional feature within this profile, whether this has been implemented in this product and tested for conformance or not.

Core

ID	Core Features	Supported / Present
C-01	Support for offline authorization of transactions	No
C-02	Support for allowing Offline Authorization for Unknown Ids	No
C-03	Support for maximizing energy for invalid ids	No
C-04	Authorization Cache	No
C-05	Support to limit StatusNotifications	No
C-06	Authorization status after cable disconnected on EV side	
C-06.1	Support for maintaining authorization when cable disconnected on EV side	No
C-06.2	Support for not maintaining authorization when cable disconnected on EV side	Yes
C-07	Support for local start	No
C-08	Support for local stop	No
C-10	Unlocking of connector when cable disconnected on EV side	
C-10.1	Support for unlocking connector when cable disconnected on EV side	No
C-10.2	Support for not unlocking when cable disconnected on EV side	Yes
C-11	Support for Security Profile 1: Unsecured Transport with Basic Authentication	Yes

ID	Metervalues	Tested During Certification	Supported According to Vendor
C-09	Supported MeterValue Measurands		

ID	Metervalues	Tested During Certification	Supported According to Vendor
C-09.1	MeterValuesSampled Data	Current.Offered Voltage Temperature Energy.Active.Import.Register SoC	Energy.Active.Import.Register, Current.Offered, SoC, Temperature, Voltage
C-09.2	MeterValuesAligned Data	Current.Offered Voltage Temperature Energy.Active.Import.Register SoC	Energy.Active.Import.Register, Current.Offered, SoC, Temperature, Voltage

ID	Cipher Suites	Supported / Present
C-12	Supported Cipher Suites	TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384

ID	Local Authorization List Management	Supported / Present
LA-0	Support for Local Authorization List Management	No

ID	Remote Trigger	Supported / Present
RT-0	Support for Remote Trigger	No

ID	Reservations	Supported / Present
R-0	Support for Reservations	No
R-1	Support reservations of entire Charging Station	No

Additional Questions

The table below lists a number of questions that are needed for determining the complete list of conformance test for this product.

ID	Additional Questions for Lab Testing	Answer
AQ-1	Can the last CentralSystemRootCertificate can be removed?	No
AQ-2	Does the Charging Station have a cable lock, which prevents the EV driver to connect the EV and EVSE before authorization?	No
AQ-3	Can the last ChargePointCertificate be removed?	No
AQ-4	Is your Charging Station able to download firmware while there is an ongoing transaction?	No
AQ-5	Does your Charging Station enforce a selection of EVSE prior to authorization?	No
AQ-6	Does your Charging Station support charging an EV using IEC 61851-1?	No
AQ-7	Reporting of StopTransaction after power loss	
AQ-7.1	Charge Point configured to report StopTransaction before going down.	No
AQ-7.2	Charge Point configured to report StopTransaction after going down and being back online again.	Yes
AQ-9	Does your Charging Station have at least one connector with an mechanized locking mechanism on Charging Station side?	No
AQ-11	Does your Charging Station support an authorization method, that does not rely on the communication between EV and Charging Station?	Yes

Other Relevant Settings

The table below lists a number of settings that are needed for configuring the test setup for the conformance test for this product.

ID	Limit / Setting	Value
ORS-1	GetConfigurationMaxKeys	49
ORS-2	MeterValuesAlignedDataMaxLength	5
ORS-3	MeterValuesSampledDataMaxLength	5
ORS-4	Minimum MeterValueSampleInterval supported	10
ORS-5	Maximum MeterValueSampleInterval supported	60
ORS-6	Minimum HeartbeatInterval supported	10
ORS-7	Maximum HeartbeatInterval supported	3600



ID	Limit / Setting	Value
ORS-8	StopTransactionMaxMeterValues	1
ORS-9	StopTxnAlignedDataMaxLength	5
ORS-10	StopTxnSampledDataMaxLength	5
ORS-11	WebSocketPingInterval	60
ORS-17	CertificateSignedMaxChainSize	1
ORS-18	CertificateStoreMaxLength	4

ID	Firmware Management Settings	Value
ORS-16	Supported file transfer protocols	FTPS

Performance Measurement Result

The tables below shows the list of key performance indicators that are measured during the conformance test. The first table indicates the values that the vendor indicates that are valid maximum values for this product. The second table lists the actual performance measurements during the tests performed in a controlled environment.

Name	Max Value	Unit	Description
OCPP response timeout	120	seconds	The timeout used for exchanging OCPP response messages. Messages to the DUT can be handled within this timeout.
OCPP triggered function timeout	120	seconds	The timeout used for when waiting for an OCPP function with its corresponding request message. Messages to the DUT can be handled within this timeout. This value excludes firmware, diagnostics and rebooting
Transaction authorization time by RemoteStartTransaction	120	seconds	The time between the RemoteStartTransaction.req message and the corresponding StartTransaction.req. Only cases where the RemoteStartTransaction immediately results in an authorization followed by a StartTransaction.req are included.
Transaction authorization end time by RemoteStopTransaction	120	seconds	The time between the RemoteStopTransaction.req message and the corresponding StopTransaction.req. Only cases where the RemoteStopTransaction immediately results in an end of the authorization followed by a StopTransaction.req are included.

Name	Min Value	Max Value	Average Value	Unit
OCPP response timeout	0.39	3.35	0.68	seconds
OCPP triggered function timeout	0.91	1.21	1.00	seconds
Transaction authorization time by RemoteStartTransaction	2.01	2.01	2.01	seconds
Transaction authorization end time by RemoteStopTransaction	7.20	7.20	7.20	seconds

Communication technology used during performance measurement	Ethernet
--	----------

Statement of Approval

Vendor		
Name	Uisong Park	Date: 2026-04-07
Company	EGTRONICS CO., LTD.	Signature:
Department	Charging business department	
Position	Pro Engineer	
Location	Hwaseong, Korea	


Test Laboratory		
Name	Hye Min Kwon	Date: 2026-04-07
Name reviewer	SOL CHO	Signature:
Company	Korea Testing Certification institute	
Department	EV Charging&Power Transfer Center	
Position	Research engineer	
Location	Gyeonggi-do, Korea	

OCTT Version	Release_2026-02
OCTT Instance ID	c37ed49892ff8133ade5b90071648a47
Firmware image hash	3603f4351fe7c7b7ca1db04a770cd6765e05793212fa86ba70f5e3f76ee47199

Product Family Members Overview

The table below lists the OCPP product family members for the Representative Product EGM205001 with Config ID 60B00282-DE45E080. For each of these individual product family members a Vendor Declaration of Conformance is attached to this document, attesting that the product family member has been successfully tested for conformance by the vendor using the same firmware as the representative product.

Vendor		
Name	Uisong Park	Date: 2026-04-07
Company	EGTRONICS CO., LTD.	Signature:
Department	Charging business department	
Position	Pro Engineer	
Location	Hwaseong, Korea	

Product Designation	Product Description	Photo
EGM1105001 Config ID: 60B00282-F3E557FB	EGTRONICS 50kW 1 Channel	


Vendor Declaration of Conformance

Product Type: Charging Station
Product Designation: EGM1105001
Firmware Version: 1.1.1.1
Test Date: April 7, 2026
Config ID: 60B00282-F3E557FB

The Vendor EGTRONICS CO., LTD. states that the above-mentioned product and software version combination successfully completed testing in conformance with the reference specification OCPP 1.6 (Edition 2 FINAL, 2017-09-28 including Errata 2025-04) and Security Whitepaper Edition 4 (Improved security for OCPP 1.6-J v1.4, 2026-02-05). The OCPP profiles and optional protocol features that were tested can be found in this Test Report.

This test report is only applicable to the product designation running the specified software version described above. On behalf of EGTRONICS CO., LTD. the undersigned declares that the OCPP conformance test was performed under his/her responsibility and that the test results were obtained by testing the above-mentioned product and software version combination using the OCPP Compliance Test Tool (OCTT) in a single uninterrupted test run without any manipulation. Note: it has not been independently verified that above-mentioned product was tested.

For EGTRONICS CO., LTD. on April 7, 2026:



Uisong Park
Pro Engineer, Charging business department, Hwaseong, Korea

Test Result Summary for the Tested Functionalities

Certification Profile	Test Result	Description
Core	Pass	Basic Charging Station, functionality for booting, authorization, configuration, transactions, remote control, secure firmware updates and Security Profile 2.
Advanced Security	Pass	Support for TLS with client authentication.
Smart Charging	Not Tested	Support for Smart Charging, to control charging.

Disclaimer: For the preparation of this Vendor Declaration, the Open Charge Alliance test tool has been used by the Vendor. The Open Charge Alliance has not been involved in the testing and or test results. Any liability of the Open Charge Alliance in respect of the tests and test results is expressly excluded. This test report shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred resulting from reliance on the results of this report.

Tested Firmware Image: 3603f4351fe7c7b77ca1db04a770cd6765e05793212fa866ba70f5e3776ee47199 - OCTT Instance ID: 900df3194d508421e6a8114f57d7e8f0

Hardware Feature Set

The Hardware Feature set is the actual set of relevant hardware properties of the product tested, that influence the OCPP messaging behavior. In the table below you can see for each hardware feature relevant for OCPP whether this is applicable for this product.

ID	Feature	Supported / Present
HFS-1	Has a detachable cable	No
HFS-2	Has a fixed cable	Yes
HFS-3	Has AC support	No
HFS-4	Has DC support	Yes
HFS-5	Has 1 phase support	No
HFS-6	Has 2 phase support	No
HFS-7	Has 3 phase support	No
HFS-8	No. Connectors	1
HFS-9	Communication technology	Ethernet
HFS-10	RFID readers	Single
HFS-11	DC power level	50

Connector	Current	Phases	Type	Cable Type
1	DC		cCCSI	Fixed Cable



Tested Firmware Image: 3603f4351fe7c7b7caldb04a770cd6765e05793212fa866ba70f5e3776ee47199 - OCTT Instance ID: 9000df3194d508421e6a8114f57a7e8f0

Optional Features

The OCPP specification contains many implementation options that can be selected by a vendor, often in the form of optional message fields or configuration variables, that can be used to support advanced functions. Whereas the certification profiles determine which OCPP functionality is implemented, the features describe how much of a certain functionality in a profile has been implemented. The tables below indicate per certification profiles, for each available optional feature within this profile, whether this has been implemented in this product and tested for conformance or not.

Core

ID	Core Features	Supported / Present
C-01	Support for offline authorization of transactions	No
C-02	Support for allowing Offline Authorization for Unknown Ids	No
C-03	Support for maximizing energy for invalid ids	No
C-04	Authorization Cache	No
C-05	Support to limit StatusNotifications	No
C-06	Authorization status after cable disconnected on EV side	
C-06.1	Support for maintaining authorization when cable disconnected on EV side	No
C-06.2	Support for not maintaining authorization when cable disconnected on EV side	Yes
C-07	Support for local start	No
C-08	Support for local stop	No
C-10	Unlocking of connector when cable disconnected on EV side	
C-10.1	Support for unlocking connector when cable disconnected on EV side	No
C-10.2	Support for not unlocking when cable disconnected on EV side	Yes
C-11	Support for Security Profile 1: Unsecured Transport with Basic Authentication	Yes

ID	Metervalues	Tested
C-09	Supported MeterValue Measurands	
C-09.1	MeterValuesSampled Data	Temperature Current.Offered Energy.Active.Import.Register Voltage SoC
C-09.2	MeterValuesAligned Data	Temperature Current.Offered Energy.Active.Import.Register Voltage SoC

ID	Cipher Suites	Supported / Present
C-12	Supported Cipher Suites	TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384

ID	Local Authorization List Management	Supported / Present
LA-0	Support for Local Authorization List Management	No

ID	Remote Trigger	Supported / Present
RT-0	Support for Remote Trigger	No

ID	Reservations	Supported / Present
R-0	Support for Reservations	No
R-1	Support reservations of entire Charging Station	No

Additional Questions

The table below lists a number of questions that are needed for determining the complete list of conformance test for this product.

ID	Additional Questions for Lab Testing	Answer
AQ-1	Can the last CentralSystemRootCertificate can be removed?	No
AQ-2	Does the Charging Station have a cable lock, which prevents the EV driver to connect the EV and EVSE before authorization?	No
AQ-3	Can the last ChargePointCertificate be removed?	No
AQ-4	Is your Charging Station able to download firmware while there is an ongoing transaction?	No
AQ-5	Does your Charging Station enforce a selection of EVSE prior to authorization?	No
AQ-6	Does your Charging Station support charging an EV using IEC 61851-1?	No
AQ-7	Reporting of StopTransaction after power loss	
AQ-7.1	Charge Point configured to report StopTransaction before going down.	No
AQ-7.2	Charge Point configured to report StopTransaction after going down and being back online again.	Yes
AQ-9	Does your Charging Station have at least one connector with a mechanized locking mechanism on Charging Station side?	No
AQ-11	Does your Charging Station support an authorization method, that does not rely on the communication between EV and Charging Station?	Yes

Other Relevant Settings

The table below lists a number of settings that are needed for configuring the test setup for the conformance test for this product.

ID	Limit / Setting	Value
ORS-1	GetConfigurationMaxKeys	49
ORS-2	MeterValuesAlignedDataMaxLength	5
ORS-3	MeterValuesSampledDataMaxLength	5
ORS-4	Minimum MeterValueSampleInterval supported	10
ORS-5	Maximum MeterValueSampleInterval supported	60
ORS-6	Minimum HeartbeatInterval supported	10
ORS-7	Maximum HeartbeatInterval supported	3600
ORS-8	StopTransactionMaxMeterValues	1
ORS-9	StopTxnAlignedDataMaxLength	5
ORS-10	StopTxnSampledDataMaxLength	5
ORS-11	WebSocketPingInterval	60
ORS-17	CertificateSignedMaxChainSize	1
ORS-18	CertificateStoreMaxLength	4

ID	Firmware Management Settings	Value
ORS-16	Supported file transfer protocols	FTPS

Test Cases

The following list contains all Test cases that are required for a full conformance test for a product that is defined as in the configuration in this document. This is the complete list of test cases for this configuration, each of these test cases has been passed using the Test System defined above. Please note that test cases that are not applicable for this configuration are left out of this list, so this is a subset of the test cases that are listed and described in the Test Case Document and Test Procedure & Test Plan document.

Testcase	Certification Profile	Name	Result
TC_001_CS	Core	Cold Boot Charge Point	PASS
TC_002_CS	Core	Cold Boot Charge Point - Pending	PASS
TC_005_2_CS	Core	EV Side Disconnected - StopTransactionOnEVSideDisconnect = true - UnlockConnectorOnEVSideDisconnect = false	PASS
TC_010_CS	Core	Remote Start Charging Session Cable Plugged in First	PASS
TC_011_1_CS	Core	Remote Start Charging Session Remote Start First	PASS
TC_011_2_CS	Core	Remote Start Charging Session Time Out	PASS
TC_012_CS	Core	Remote Stop Charging Session	PASS
TC_013_CS	Core	Hard Reset Without transaction	PASS
TC_014_CS	Core	Soft Reset Without Transaction	PASS
TC_015_CS	Core	Hard Reset With Transaction	PASS
TC_016_CS	Core	Soft Reset With Transaction	PASS
TC_017_2_CS	Core	Unlock connector - no charging session running	PASS
TC_018_2_CS	Core	Unlock Connector - With Charging Session	PASS
TC_019_CS	Core	Retrieve configuration	PASS
TC_021_CS	Core	Change/set Configuration	PASS
TC_070_CS	Core	Sampled Meter Values	PASS
TC_071_CS	Core	Clock-aligned Meter Values	PASS
TC_026_CS	Core	Remote Start Charging Session Rejected	PASS
TC_028_CS	Core	Remote Stop Transaction Rejected	PASS
TC_031_CS	Core	Unlock Connector Unknown Connector	PASS
TC_032_2_CS	Core	Power failure boot charging point-configured to stop transaction	PASS
TC_034_CS	Core	Power Failure with Unavailable Status	PASS
TC_036_CS	Core	Connection Loss During Transaction	PASS
TC_040_1_CS	Core	Configuration key - NotSupported	PASS
TC_040_2_CS	Core	Configuratioin key - Invalid value	PASS
TC_042_1_CS	Core	Get Local List Version	PASS
TC_043_1_CS	Core	Send Local Authorization List - NotSupported	PASS
TC_045_1_CS	Core	Get Diagnostics	PASS
TC_045_2_CS	Core	Get Diagnostics - Upload Failed	PASS
TC_073_CS	Core	Update Charge Point Password for HTTP Basic Authentication	PASS
TC_075_1_CS	Core	Install a certificate on the Charge Point - ManufacturerRootCertificate	PASS

Tested Firmware Image: 3603f4351fe7c7b7caldb04a770cd6765e05793212fa86ba70f5e3776ee47199 - OCTT Instance ID: 900df3194d508421e6a8114f57d7e8f0

Testcase	Certification Profile	Name	Result
TC_075_2_CS	Core	Install a certificate on the Charge Point - CentralSystemRootCertificate	PASS
TC_076_CS	Core	Delete a specific certificate from the Charge Point	PASS
TC_078_CS	Core	Invalid CentralSystemCertificate Security Event	PASS
TC_079_CS	Core	Get Security Log	PASS
TC_080_CS	Core	Secure Firmware Update	PASS
TC_081_CS	Core	Secure Firmware Update - Invalid Signature	PASS
TC_083_CS	Core	Upgrade security profile	PASS
TC_084_CS	Core	Downgrade security profile - Rejected	PASS
TC_085_CS	Core	Basic Authentication - Valid username/password combination	PASS
TC_086_CS	Core	TLS - server-side certificate - Valid certificate	PASS
TC_062_CS	Core	Data Transfer to a Charge Point	PASS
TC_074_CS	Advanced Security	Update Charge Point Certificate by request of Central System	PASS
TC_077_CS	Advanced Security	Invalid ChargePointCertificate Security Event	PASS
TC_087_CS	Advanced Security	TLS - Client-side certificate - valid certificate	PASS

Tested Firmware Image: 3603f4351fe7c7b7caldb04a770cd6765e05793212fa866ba70f5e3776ee47199 - OCTT Instance ID: 9000df3194d508421e6a8114f57a7e8f0