



**Certificate Holder:** Everon Co., Ltd.  
**Certificate Number:** OCA.0201.0156.CS  
**Product Type:** Charging Station  
**Product Designation:** Everon-Kiosk-201  
**Firmware Version:** KA100-OCPP201-Core-1.0.0  
**Certification Date:** May 13, 2026

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 2.0.1 (Edition 4 FINAL, 2025-12-03 including Errata 2026-04). The optional OCPP protocol features that are covered by this certificate can be found in the Abstract of the Test Report that is part of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in this complete test report.

Applied	Performed by / On	Document Evidence
Conformance testing according to the test specification referenced by the test report	Korea Smart Grid Association May 13, 2026	EVERON_PICS 2.0.1 CS_Everon-Kiosk-201_v3. 0.3

The abstract of test report is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

**ONOPH CARON**  
Chairman

## Abstract of the Test Report

### Test Report OCPP 2.0.1 Certification

<b>Test laboratory:</b>	<b>Korea Smart Grid Association</b>
Location:	Seoul, Korea
Test Report Reference:	KSGA-OCPP2.0.ITEST-002-2026
Test Location	KAVIC
<b>Product Designation:</b>	<b>Everon-Kiosk-201</b>
Vendor name:	Everon Co., Ltd.
Device Under Test:	Charging Station
Firmware Version:	KA100-OCPP201-Core-1.0.0
Config ID:	811AAC6-8393D8E2

### Test Result Summary for the Certified Functionalities

Certification Profile	Test Result	Description
Core	Pass	Basic Charging Station, functionality for booting, authorization, configuration, transactions, remote control, secure firmware updates and Security Profile 2.
Advanced Security	Not Tested	Support for TLS with client authentication.
Smart Charging	Not Tested	Support for Smart Charging, to control charging.
ISO 15118 Support	Not Tested	Support for ISO 15118 Smart Charging and Plug and Charge authorization.

## Hardware Feature Set

The Hardware Feature set is the actual set of relevant hardware properties of the product tested, that influence the OCPP messaging behavior. In the table below you can see for each hardware feature relevant for OCPP whether this is applicable for this product.

ID	Feature	Supported / Present
HFS-1	Has a detachable cable	No
HFS-2	Has a fixed cable	Yes
HFS-3	Has AC support	No
HFS-4	Has DC support	Yes
HFS-5	Has 1 phase support	No
HFS-6	Has 2 phase support	No
HFS-7	Has 3 phase support	No
HFS-8	No. EVSEs	1
HFS-9	Communication technology	Ethernet
HFS-10	RFID readers	None
HFS-11	DC power level	100
HFS-12	Number of displays	1

EVSE	Current	Phases	Connector	Type	Cable Type
1	DC		1	cCCSI	Fixed Cable



## Optional Features

The OCPP specification contains many implementation options that can be selected by a vendor, often in the form of optional message fields or configuration variables, that can be used to support advanced functions. Whereas the certification profiles determine which OCPP functionality is implemented, the features describe how much of a certain functionality in a profile has been implemented. The tables below indicate per certification profiles, for each available optional feature within this profile, whether this has been implemented in this product and tested for conformance or not. Please refer to part 5 of the OCPP specification for the list of optional features and the reference to the relevant use cases in part 2 of the OCPP specification.

### Core

ID	Core Features	Supported / Present
C-01	Support for offline authorization of transactions	No
C-02	Support for allowing Offline Authorization for Unknown Ids	No
C-03	Support for maximizing energy for invalid ids	No
C-04	Support to limit StatusNotifications	No
C-06	Authorization status after cable disconnected on EV side	
C-06.1	Support for maintaining authorization when cable disconnected on EV side	No
C-06.2	Support for not maintaining authorization when cable disconnected on EV side	Yes
C-07	Support for using a Master Pass for charging stations with UI	No
C-08	Support for using a Master Pass for charging stations without UI	No
C-09	Supported Transaction Start points	
C-09.1	Start transaction options - EVConnected	No
C-09.2	Start transaction options - Authorized	No
C-09.3	Start transaction options - DataSigned	No
C-09.4	Start transaction options - PowerPathClosed	Yes
C-09.5	Start transaction options - EnergyTransfer	No
C-09.6	Start transaction options - ParkingBayOccupancy	No
C-10	Supported Transaction Stop points	
C-10.1	Stop transaction options - EVConnected	No
C-10.2	Stop transaction options - Authorized	No
C-10.3	Stop transaction options - PowerPathClosed	Yes
C-10.4	Stop transaction options - EnergyTransfer	No
C-10.5	Stop transaction options - ParkingBayOccupancy	No
C-12	Unlocking of connector when cable disconnected on EV side	

ID	Core Features	Supported / Present
C-12.1	Support for unlocking connector when cable disconnected on EV side	No
C-12.2	Support for not unlocking when cable disconnected on EV side	Yes
C-13	Support for Reset per EVSE	No
C-14	Support for retrieving / deleting CustomerInformation - CustomerIdentifier	No
C-20	Allowing New Sessions Pending a FirmwareUpdate	No
C-21	Support for queuing all or only Transaction related messages until they are delivered to the CSMS	No
C-23	Supported time sources	Heartbeat
C-25	Support for setting a TimeOffset	No
C-26	Support for setting the TimeZone	No
C-28	Toggle sending clock aligned meter values when a transaction is ongoing / Idle	No
C-29	TriggerMessage	
C-29.1	Trigger message - MeterValues	No
C-29.2	Trigger message - TransactionEvent	No
C-29.3	Trigger message - LogStatusNotification	No
C-29.4	Trigger message - FirmwareStatusNotification	No
C-29.5	Trigger message - StatusNotification	No
C-29.6	Trigger message - BootNotification	No

ID	Authorization Options for Local Start	Tested During Certification
C-30	Authorization - using RFID ISO14443	No
C-31	Authorization - using RFID ISO15693	No
C-32	Authorization - using KeyCode	No
C-33	Authorization - using locally generated id	No
C-34	Authorization - MacAddress	No
C-35	Authorization - NoAuthorization	No

ID	Authorization Options for Local Stop	Tested During Certification
C-70	Authorization - using RFID ISO14443	No
C-71	Authorization - using RFID ISO15693	No
C-72	Authorization - using KeyCode	No
C-75	Authorization - NoAuthorization	No

ID	Authorization Options for Remote Start	Tested During Certification
C-36	Authorization - using RFID ISO14443	Yes
C-37	Authorization - using RFID ISO15693	No
C-38	Authorization - using centrally, in the CSMS generated id	No
C-39	Authorization - NoAuthorization	No

ID	Metervalues	Tested During Certification	Supported According to Vendor
C-40	Supported MeterValue Measurands		
C-40.1	SampledTxBegan Measurands	Energy.Active.Import.Register	Energy.Active.Import.Register
C-40.2	SampledTxBegan Measurands	Energy.Active.Import.Register	Energy.Active.Import.Register
C-40.3	SampledTxBegan Measurands	Energy.Active.Import.Register	Energy.Active.Import.Register
C-40.4	AlignedData Measurands	Energy.Active.Import.Register	Energy.Active.Import.Register
C-40.5	AlignedDataTxEnded Measurands	Energy.Active.Import.Register	Energy.Active.Import.Register

ID	Cipher Suites	Supported / Present
C-41	Supported Cipher Suites	TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384

ID	Core Features	Supported / Present
C-42	Signed Metervalues	No
C-43	Install Firmware with ongoing transaction	No
C-47	Support for falling back to default OCPP reconnection mechanism when NetworkConnection profile connection has failed	No
C-48	Authorization of remote start	
C-48.1	Option for authorization in case of a remote start	No
C-48.2	Option for no authorization in case of a remote start	Yes
C-58	Option for disabling remote authorization	No

ID	Core Features	Supported / Present
C-49	Authorization Cache	No
C-59	Option for disabling remote authorization for cached invalid idTokens	No
C-51	Configurable TxStartPoint	No
C-52	Configurable TxStopPoint	No
C-53	Support for lifetime cached token	No
C-54	Supported policies for replacing cached entries	No
C-56	Support for providing the SummaryInventory	No
C-57	Support for cancelling ongoing log file upload	No
C-60	Support for cancelling ongoing firmware update	No
C-61	Security Profile 1 - Unsecured Transport with Basic Authentication	No

ID	Reservations	Supported / Present
R-0	Support for Reservation	No
R-1	Support for reservations of connectorType	No
R-2	Support for reservation of unspecified EVSE	No
R-3	Support for disabling Reservations	No

ID	Advanced Device Management	Supported / Present
DM-0	Support for Advanced Device Management	No
DM-3	Queue notifyEventRequest messages for specific severities	No

ID	Local Authorization List Management	Supported / Present
LA-0	Support for Local Authorization List Management	No
LA-1	Authorization list support	No
LA-3	Option for disabling remote authorization for invalid idTokens stored at the Local Authorization List	No

ID	Advanced User Interface	Supported / Present
UI-0	Support for Advanced User Interface	No

ID	Advanced User Interface	Supported / Present
UI-1	Supported message priorities	
UI-1.1	AlwaysFront	No
UI-1.2	InFront	No
UI-1.3	NormalCycle	No
UI-2	Supported message formats	
UI-2.1	ASCII	No
UI-2.2	HTML	No
UI-2.3	URI	No
UI-2.4	UTF8	No

### ISO 15118 Support

ID	Certification Profile: ISO 15118 Support	Supported / Present
ISO-4	Support for retrieving / deleting CustomerInformation - CustomerCertificate	No
ISO-5	Charging Station can provide a contract certificate that it cannot validate to the CSMS	No

### Additional Questions

The table below lists a number of questions that are needed for determining the complete list of conformance test for this product.

ID	Additional Questions for Lab Testing	Answer
AQ-1	Can the last CSMSRootCertificate be removed?	No
AQ-2	Does the Charging Station have a cable lock, which prevents the EV driver to connect the EV and EVSE before authorization?	No
AQ-3	Can the last ChargingStationCertificate be removed?	No
AQ-4	Is there at least one unsupported NumberOfPhases?	No
AQ-5	Does the Charging Station have at least one hardWired monitor?	No
AQ-6	Does the Charging Station have a pre-configured monitor?	No
AQ-7	Is your Charging Station able to download firmware while there is an ongoing transaction?	No

ID	Additional Questions for Lab Testing	Answer
AQ-8	Does your Charging Station enforce a selection of EVSE prior to authorization?	No
AQ-9	Does your Charging Station support charging an EV using IEC 61851-1?	No
AQ-10	Does your Charging Station support setting a Delta monitor on the WriteOnly component.variable SecurityCtrlr.BasicAuthPassword?	No
AQ-11	Does your Charging Station support a combined charging station Certificate	No
AQ-18	Does your Charging Station have at least one connector with an mechanized locking mechanism on Charging Station side?	No

### Other Relevant Settings

The table below lists a number of settings that are needed for configuring the test setup for the conformance test for this product.

ID	Limit / Setting	Value
ORS-1	ItemsPerMessageGetReport	5
ORS-2	ItemsPerMessageGetVariables	5
ORS-3	ItemsPerMessageSetVariables	5
ORS-4	BytesPerMessageGetReport	1024
ORS-5	BytesPerMessageGetVariables	1024
ORS-6	BytesPerMessageSetVariables	1024
ORS-7	Minimum MessageAttemptIntervalTransactionEvent supported	5
ORS-8	Maximum MessageAttemptIntervalTransactionEvent supported	60
ORS-9	Minimum SampledDataTxUpdatedInterval supported	1
ORS-10	Maximum SampledDataTxUpdatedInterval supported	60
ORS-11	Minimum HeartbeatInterval supported	10
ORS-12	Maximum HeartbeatInterval supported	300
ORS-14	Minimum WebSocketPingInterval supported	10
ORS-15	Maximum WebSocketPingInterval supported	120
ORS-16	WebSocketPingInterval	60

ID	Security Related Settings	Value
ORS-17	Maximum CertificateEntries supported	1
ORS-18	MaxCertificateChainSize	3

ID	Firmware Management Settings	Value
ORS-24	Supported file transfer protocols	FTP

## Performance Measurement Result

The tables below shows the list of key performance indicators that are measured during the conformance test. The first table indicates the values that the vendor indicates that are valid maximum values for this product. The second table lists the actual performance measurements during the tests performed in a controlled environment.

Name	Max Value	Unit	Description
OCPP response time	10	seconds	The response time for when waiting for an OCPP response message after sending an OCPP request message. This entails all OCPP messages. Messages to the DUT can be handled within this timeout.
OCPP triggered function response time	10	seconds	The response time used when waiting for an asynchronous OCPP report after requesting this report.
Transaction authorization time by RequestStartTransactionRequest	10	seconds	The time between a RequestStartTransactionRequest and the corresponding TransactionEventRequest. Only cases where the RequestStartTransactionRequest immediately results in an authorization followed by a TransactionEventRequest, without the need of any additional manual actions or chargingState transitions inbetween are included.
Transaction authorization end time by RequestStopTransactionRequest	10	seconds	The time between a RequestStopTransactionRequest and the corresponding TransactionEventRequest. Only cases where the RequestStopTransactionRequest immediately results in an end of the authorization followed by a TransactionEventRequest, that do not contain transactionInfo.chargingState = EVConnected are included.

Name	Min Value	Max Value	Average Value	Unit
OCPP response time	0.28	0.40	0.29	seconds
OCPP triggered function response time	0.30	5.24	4.02	seconds
Transaction authorization time by RequestStartTransactionRequest	0.40	0.53	0.45	seconds
Transaction authorization end time by RequestStopTransactionRequest	not measurable	not measurable	not measurable	seconds

Communication technology used during performance measurement	Ethernet
--	----------

## Statement of Approval

Vendor		
Name	Sanguk Park	Date: 2026-05-13
Company	Everon Co., Ltd.	Signature:
Department	-	
Position	-	
Location	Seoul, Korea	

Test Laboratory		
Name	Philip YANG	Date: 2026-05-13
Name reviewer	Joe Lee	Signature:
Company	Korea Smart Grid Association	
Department	Quality Certification Center	
Position	Chief Researcher	
Location	Seoul, Korea	

OCTT Version	Release_2026-04
OCTT Instance ID	7a4beba641b8341e27a88c78d48bf4aa
Firmware image hash	6fbcdf37dda9c6f5e6626d083856bf14999daf15497c47e09386c0b3b9e63c2