



Certificate Holder: Sevasa Inc.
Certificate Number: OCA.0016.1247.CS
Product Type: Charging Station
Product Designation: SVS-C007-TWA
Firmware Version: v1.10
Certification Date: May 29, 2026

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 (Edition 2 FINAL, 2017-09-28 including Errata 2025-04) and Security Whitepaper Edition 4 (Improved security for OCPP 1.6-J v1.4, 2026-02-05). The optional OCPP protocol features that are covered by this certificate can be found in the Abstract of the Test Report that is part of this certificate.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in this complete test report.

| Applied | Performed by / On | Document Evidence |
|---|--|--|
| Conformance testing according to the test specification referenced by the test report | Korea Testing Laboratory May 12, 2026 | OCPP-1.6-PICS-CS-3.0.6_ Sevasa_KTL_26-029811-0 1-1 |

The abstract of test report is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON
Chairman

Abstract of the Test Report

Test Report OCPP 1.6 Certification

| | |
|-----------------------------|---------------------------------|
| Test laboratory: | Korea Testing Laboratory |
| Location: | Seoul, Korea |
| Test Report Reference: | KTL_26-029811-01-1 |
| Test Location | KTL Test Lab |
| Product Designation: | SVS-C007-TWA |
| Vendor name: | Sevasa Inc. |
| Device Under Test: | Charging Station |
| Firmware Version: | v1.10 |
| Config ID: | 660D0496-AF659817 |

Test Result Summary for the Certified Functionalities

| Certification Profile | Test Result | Description |
|-----------------------|-------------|--|
| Core | Pass | Basic Charging Station, functionality for booting, authorization, configuration, transactions, remote control, secure firmware updates and Security Profile 2. |
| Advanced Security | Not Tested | Support for TLS with client authentication. |
| Smart Charging | Not Tested | Support for Smart Charging, to control charging. |

Hardware Feature Set

The Hardware Feature set is the actual set of relevant hardware properties of the product tested, that influence the OCPP messaging behavior. In the table below you can see for each hardware feature relevant for OCPP whether this is applicable for this product.

| ID | Feature | Supported / Present |
|--------|--------------------------|---------------------|
| HFS-1 | Has a detachable cable | No |
| HFS-2 | Has a fixed cable | Yes |
| HFS-3 | Has AC support | Yes |
| HFS-4 | Has DC support | No |
| HFS-5 | Has 1 phase support | Yes |
| HFS-6 | Has 2 phase support | No |
| HFS-7 | Has 3 phase support | No |
| HFS-8 | No. Connectors | 1 |
| HFS-9 | Communication technology | Mobile network |
| HFS-10 | RFID readers | Single |

| Connector | Current | Phases | Type | Cable Type |
|-----------|---------|--------|--------|-------------|
| 1 | AC | 1 | cType1 | Fixed Cable |



Optional Features

The OCPP specification contains many implementation options that can be selected by a vendor, often in the form of optional message fields or configuration variables, that can be used to support advanced functions. Whereas the certification profiles determine which OCPP functionality is implemented, the features describe how much of a certain functionality in a profile has been implemented. The tables below indicate per certification profiles, for each available optional feature within this profile, whether this has been implemented in this product and tested for conformance or not.

Core

| ID | Core Features | Supported / Present |
|--------|---|---------------------|
| C-01 | Support for offline authorization of transactions | No |
| C-02 | Support for allowing Offline Authorization for Unknown Ids | No |
| C-03 | Support for maximizing energy for invalid ids | No |
| C-04 | Authorization Cache | No |
| C-05 | Support to limit StatusNotifications | No |
| C-06 | Authorization status after cable disconnected on EV side | |
| C-06.1 | Support for maintaining authorization when cable disconnected on EV side | No |
| C-06.2 | Support for not maintaining authorization when cable disconnected on EV side | Yes |
| C-07 | Support for local start | Yes |
| C-08 | Support for local stop | Yes |
| C-10 | Unlocking of connector when cable disconnected on EV side | |
| C-10.1 | Support for unlocking connector when cable disconnected on EV side | No |
| C-10.2 | Support for not unlocking when cable disconnected on EV side | Yes |
| C-11 | Support for Security Profile 1: Unsecured Transport with Basic Authentication | Yes |

| ID | Metervalues | Tested During Certification | Supported According to Vendor |
|--------|---------------------------------|--|--|
| C-09 | Supported MeterValue Measurands | | |
| C-09.1 | MeterValuesSampled Data | Energy.Active.Import.Register Energy.Active.Import.Interval | Energy.Active.Import.Register Energy.Active.Import.Interval |
| C-09.2 | MeterValuesAligned Data | Energy.Active.Import.Register Energy.Active.Import.Interval | Energy.Active.Import.Register Energy.Active.Import.Interval |

| ID | Cipher Suites | Supported / Present |
|------|-------------------------|--|
| C-12 | Supported Cipher Suites | TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384 |

| ID | Local Authorization List Management | Supported / Present |
|------|---|---------------------|
| LA-0 | Support for Local Authorization List Management | No |

| ID | Remote Trigger | Supported / Present |
|------|----------------------------|---------------------|
| RT-0 | Support for Remote Trigger | No |

| ID | Reservations | Supported / Present |
|-----|---|---------------------|
| R-0 | Support for Reservations | No |
| R-1 | Support reservations of entire Charging Station | No |

Additional Questions

The table below lists a number of questions that are needed for determining the complete list of conformance test for this product.

| ID | Additional Questions for Lab Testing | Answer |
|--------|--|--------|
| AQ-1 | Can the last CentralSystemRootCertificate can be removed? | No |
| AQ-2 | Does the Charging Station have a cable lock, which prevents the EV driver to connect the EV and EVSE before authorization? | No |
| AQ-3 | Can the last ChargePointCertificate be removed? | No |
| AQ-4 | Is your Charging Station able to download firmware while there is an ongoing transaction? | No |
| AQ-5 | Does your Charging Station enforce a selection of EVSE prior to authorization? | No |
| AQ-6 | Does your Charging Station support charging an EV using IEC 61851-1? | No |
| AQ-7 | Reporting of StopTransaction after power loss | |
| AQ-7.1 | Charge Point configured to report StopTransaction before going down. | No |

| ID | Additional Questions for Lab Testing | Answer |
|--------|--|--------|
| AQ-7.2 | Charge Point configured to report StopTransaction after going down and being back online again. | Yes |
| AQ-9 | Does your Charging Station have at least one connector with a mechanized locking mechanism on Charging Station side? | No |
| AQ-11 | Does your Charging Station support an authorization method, that does not rely on the communication between EV and Charging Station? | Yes |

Other Relevant Settings

The table below lists a number of settings that are needed for configuring the test setup for the conformance test for this product.

| ID | Limit / Setting | Value |
|--------|--|--------|
| ORS-1 | GetConfigurationMaxKeys | 3 |
| ORS-2 | MeterValuesAlignedDataMaxLength | 1 |
| ORS-3 | MeterValuesSampledDataMaxLength | 1 |
| ORS-4 | Minimum MeterValueSampleInterval supported | 5 |
| ORS-5 | Maximum MeterValueSampleInterval supported | 540 |
| ORS-6 | Minimum HeartbeatInterval supported | 20 |
| ORS-7 | Maximum HeartbeatInterval supported | 300 |
| ORS-8 | StopTransactionMaxMeterValues | 999999 |
| ORS-11 | WebSocketPingInterval | 60 |

| ID | Firmware Management Settings | Value |
|--------|-----------------------------------|-------------|
| ORS-16 | Supported file transfer protocols | HTTP FTP |

Performance Measurement Result


The tables below shows the list of key performance indicators that are measured during the conformance test. The first table indicates the values that the vendor indicates that are valid maximum values for this product. The second table lists the actual performance measurements during the tests performed in a controlled environment.

| Name | Max Value | Unit | Description |
|---|-----------|---------|---|
| OCPP response timeout | 30 | seconds | The timeout used for exchanging OCPP response messages. Messages to the DUT can be handled within this timeout. |
| OCPP triggered function timeout | 30 | seconds | The timeout used for when waiting for an OCPP function with its corresponding request message. Messages to the DUT can be handled within this timeout. This value excludes firmware, diagnostics and rebooting |
| Transaction authorization time by RemoteStartTransaction | 10 | seconds | The time between the RemoteStartTransaction.req message and the corresponding StartTransaction.req. Only cases where the RemoteStartTransaction immediately results in an authorization followed by a StartTransaction.req are included. |
| Transaction authorization end time by RemoteStopTransaction | 10 | seconds | The time between the RemoteStopTransaction.req message and the corresponding StopTransaction.req. Only cases where the RemoteStopTransaction immediately results in an end of the authorization followed by a StopTransaction.req are included. |

| Name | Min Value | Max Value | Average Value | Unit |
|---|-----------|-----------|---------------|---------|
| OCPP response timeout | 0.53 | 2.27 | 1.19 | seconds |
| OCPP triggered function timeout | 0.80 | 0.87 | 0.83 | seconds |
| Transaction authorization time by RemoteStartTransaction | 2.81 | 2.81 | 2.81 | seconds |
| Transaction authorization end time by RemoteStopTransaction | 0.87 | 0.87 | 0.87 | seconds |

| | |
|--|----------------|
| Communication technology used during performance measurement | Mobile Network |
|--|----------------|

Statement of Approval

| Vendor | | |
|------------|--|---|
| Name | lee hye won | Date: 2026-05-29 |
| Company | Sevasa Inc. | Signature: |
| Department | R&D Center |  |
| Position | Engineer | |
| Location | Room 805, Startup Support Center, 11-41, Simin-daero 327beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, Korea | |

| Test Laboratory | | |
|-----------------|----------------------------------|---|
| Name | Seoung Hoon Jeong | Date: 2026-05-29 |
| Name reviewer | Ah Han | Signature: |
| Company | Korea Testing Laboratory |  |
| Department | IT Convergence Technology Center | |
| Position | Senior Research Engineer | |
| Location | Seoul, Korea | |

| | |
|---------------------|--|
| OCTT Version | Release_2026-04 |
| OCTT Instance ID | 74c6d1d36994375a058b276c764533a9 |
| Firmware image hash | c2e52810a6cd49937a7a2515ca4c3belccae276b7eea34644e90dleele7b6cd1 |